

OptiChannel

Indoor Distribution Cable

Riser



- Features
- E-Z Strip Buffer For Contractor-Friendly Termination
  - Compact Cable Diameter Reduces Pathway Congestion
  - Premium Bend-Insensitive Fiber For Enhanced Optical Performance

Ordering Information

| Description                                             | Fiber Type    | Catalog No. | UPC No.      |
|---------------------------------------------------------|---------------|-------------|--------------|
| Indoor Tight Buffer Distribution, 12 Fiber, Riser, Aqua | OM4 Multimode | HFCD1012R4  | 662620333632 |

Listings

ANSI/ICEA S-83-596  
TIA-568.3-D  
NFPA-262/UL910/CSA FT-6  
Telcordia GR-409 and GR-20

Specifications

|                        |                                     |
|------------------------|-------------------------------------|
| Fiber Coating          | 900 Micron PVC Tight Buffer         |
| Cable Diameter in (mm) | 0.25 (6.3)                          |
| Cable Weight (lb/kft)  | 35                                  |
| Construction           | Single Unit, Aramid Strength Member |
| Aarmor                 | None                                |

Performance

Cable Attenuation (dB/km at 850/1300 nm)

3.5/1.5

Maximum Installation Pulling Load (lb)

160

Maximum Operating Temperature

-4°F to +158°F (-20°C to +70°C)

Minimum Bend Radius, In-Service in (cm)

2.3 (5.8)



Accessories

|                           |             |
|---------------------------|-------------|
| Fiber Strip Tool          | OFSTRIP2    |
| Splice Tray, 12 Fusion    | STRAY12F    |
| Splice Tray, 24 Fusion    | STRAY24F    |
| Splice Protection Sleeves | FSHST401025 |

Online Resources

eCatalog

