




Screw-Screwless Connectors

900-07 RZ/10 DS

Terminal Block, 10 pole, Fixing: Catch Pin, Wire Protector (DS): yes, Clamping Units per Pole: 2, Voltage Rating: 450 V, Current Rating: 17.5 A, Cross-Section Rating External: 2.5 mm², Cross-Section Rating Internal: 1.5 mm²



Order Info

Reference Number (ref. no.)	114910
Applications	Lighting, Electrical Appliances
PU	250

Type

Type	Terminal Block
Number of poles	10 pole
Clamping Units per Pole	2
Colour	white
Cross-Section	1.5 / 2.5 mm ²
Connection Type	Screw-screwless
Wire Protector (DS)	yes

Technical Data

Voltage Rating	450 V
Current Rating	17.5 A
Insulating Material	PA 6.6
Contact Material	Spring Steel, Steel
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Assembly Contact Screw	0.8x4.0 / ⚙ 0.5 Nm
Internal Core Cross-Section max.	2.5 mm ²
Internal Stripping Length	7.0-7.5 mm
External Stripping Length	8.0-8.5 mm
Fixing	Catch Pin
Internal Core Cross-Section min.	0.5 mm ²
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes
Cross-Section Rating External	2.5 mm ²

Cross-Section Rating Internal	1.5 mm ²
--------------------------------------	---------------------

Accessories

ZEL 110	196420
----------------	--------