





THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
	A1	REVISED PER ECO-08-014051	09JUN08	HMR	CR	



MATERIALS:
HOUSING: PA66, UL94V-0, GREEN
CAGE: BRASS, NICKEL PLATED
CLAMP: PHOS BRONZE, NICKEL PLATED
SCREW: STEEL, ZIINC PLATED

ELECTRICAL:
CURRENT RATING: 8A
VOLTAGE RATING: 300V
INSULATION RESISTANCE: 5000Mohm/DC1000V
WITHSTANDING VOLTAGE: AC2000V/1 MIN
WIRE RANGE: 16-28 AWG

MECHANICAL:
MAXIMUM SCREW TORQUE: 2.04 kgf.cm
OPERATING TEMP.: -40°C TO 105°C

- 1 PRELIMINARY PART NUMBER.
- 2 LOGOS TO BE SHOWN APPROXIMATELY AS SHOWN

1	28.00±0.30	32.30±0.30	9	1776952-9
1	24.50±0.30	28.80±0.20	8	1776952-8
1	14.00±0.25	18.30±0.20	5	1776952-5
	10.50±0.25	14.80±0.20	4	1776952-4
1	7.00±0.15	11.30±0.20	3	1776952-3
1	3.50±0.10	7.80±0.20	2	1776952-2
	DIM B	DIM A	NO OF POS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S SCHLEGEL 30MAR2007	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm		CHK C RICHARD 3/30/07		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD C RICHARD 3/30/07	NAME TERMINAL BLOCK, R/A PLUG, 3.50mm PITCH	
0 PLC ± - 1 PLC ± 0.2 2 PLC ± 0.10 3 PLC ± - 4 PLC ± - ANGLES ± 1°		PRODUCT SPEC -		
MATERIAL -		APPLICATION SPEC -	SIZE A300779	
FINISH -		WEIGHT -		
CUSTOMER DRAWING			SCALE NTS	SHEET 1 OF 1
			REV A1	