
This document was generated on 06/08/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0855687886
Status: Active
Overview: modular_plugs_jacks
Description: Modular Plug, Short Body, Shielded, 8/8, Blue Boot, Cat6



Series image - Reference only

Documents:

- 3D Model
- Drawing (PDF)
- Product Specification PS-85568-001 (PDF)
- RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E107635

General

Product Family	Modular Jacks/Plugs
Series	85568
Component Type	Wire Plug
Magnetic	No
Overview	modular_plugs_jacks
Performance Category	6
Power over Ethernet (PoE)	N/A
Product Name	RJ45

Physical

Boot Color	BLUE
Color - Resin	Clear
Durability (mating cycles max)	750
Flammability	94V-0
Inverted / Top Latch	N/A
Lightpipes/LEDs	None
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin-Lead
Material - Resin	Polycarbonate
Orientation	N/A
PCB Locator	No
PCB Retention	None
Packaging Type	Bag
Pitch - Mating Interface (in)	0.040 In
Pitch - Mating Interface (mm)	1.02 mm
Pitch - Term. Interface (in)	0.040 In
Pitch - Term. Interface (mm)	1.02 mm
Plating min: Mating (µin)	12
Plating min: Mating (µm)	0.3
Plating min: Termination (µin)	50.8
Plating min: Termination (µm)	1.27
Ports	1
Positions / Loaded Contacts	8/8
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-40°C to +80°C
Termination Interface: Style	IDT or Pierce
Waterproof / Dustproof	No
Wire/Cable Type	Round

Electrical

Current - Maximum per Contact	1.5A

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Halogen-Free Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
85568Series

Mates With
FCC 68 Jacks

Application Tooling | **FAQ**

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Handtool for 85568 Telecom Plug, Type C Crimp with Diameter 6.0 Cable	0690081192


Grounding to Panel	N/A
Shielded	Yes
Voltage - Maximum	125V AC (RMS)

Material Info


Reference - Drawing Numbers


Application Specification	AS-85568-002
Packaging Specification	PK-85568-001
Product Specification	PS-85568-001
Sales Drawing	SD-85568-001

This document was generated on 06/08/2010
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



SHIELD ASSEMBLED ONTO HOUSING





NOTES:

1- MATERIAL:
   PLUG HOUSING:
      CLEAR POLYCARBONATE UL94 V0
   WIRE-MANAGER:
      CLEAR POLYCARBONATE UL94 V0
   TERMINALS:
      PHOSPHOR BRONZE PLATED WITH 0.00127/.00005 MIN. GOLD IN CONTACT AREA, 0.00127/.00005 MIN. THIN LEAD IN PIERCE AREA BOTH OVER 0.00127/.00005 MIN. NICKEL
   SHIELD:
      COPPER ALLOY PLATED WITH 0.00254/.000100 MIN. BRIGHT TIN OVER 0.00127/.00005 MIN. NICKEL
2- PRODUCT INTENDED TO TERMINATE
   ROUND SHIELDED PIMF CABLE
   WITH JACKET O.D.: 5.9 +0.2 -0.3/ .232 +.008 -.012
   AS PER APPLICATION SPECIFICATION
   APPLICATION TOOLING- HAND TOOL:69008-1192
   DIE SET:69008-1193
3- PRODUCT SPECIFICATION: PS-85568-001
4- APPLICATION SPECIFICATION: AS-85568-002
5- PACKAGING SPECIFICATION: PK-85568-001
6- MATING INTERFACE DIMENSIONS OF PLUG ACC. IEC 60603-7-1 FREE CONNECTOR-VARIANT 02

REV	DESCRIPTION	APPR:	CHK'D:	DRWN:	EC NO:
A	APP TOOLING ADDED TO NOTE 6	EOMAHONY 2007/03/23	2007/03/23	PGRADY	E2007-0831 2007/03/23

QUALITY SYMBOLS
▼=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)


	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.25	± .010
1 PLACE	± ---	± ---

ANGULAR ± .5 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS


DIMENSION STYLE	MM/IN
SCALE	5:1
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	SSTEINKE 2002/10/01
CHECKED BY / DATE	SFILIPON 2002/10/08
APPROVED BY / DATE	MHEIM 2002/10/08
TITLE	SHIELDED MOD. PLUG CAT.6 8 POS. WITH WIRE MANAGER ROUND CABLE
	MOLEX INCORPORATED
MATERIAL NO.	SEE SHEET 2
DOCUMENT NO.	SD-85568-001
SHEET NO.	1 OF 2
SIZE	A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



SHIELDED PLUG COMPOSITION

ASSEMBLY PART NUMBER	BOOT WITH LATCH PROTECTION			PARTS/ UNIT	PACKAGING VERSION
	PART NUMBER	COLOR	RAL NBR		
85568-7880	NO BOOT			1	A
85568-7881	95115-4881	BLACK	9005	1	A
85568-7882	95115-4882	GREY	7012	1	A
85568-7883	95115-4883	GREEN	6016	1	A
85568-7884	95115-4884	RED	3000	1	A
85568-7885	95115-4885	YELLOW	1021	1	A
85568-7886	95115-4886	BLUE	5015	1	A
85568-7887	95115-4887	ORANGE	2004	1	A



EC NO: E2007-0831 2007/03/23
DRWN:PGRADY 2007/03/23
CHKD:
APPR:EOMAHONY 2007/03/23
DESCRIPTION
REV A

QUALITY SYMBOLS
▼=0
Ⓒ=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.25	± .010
1 PLACE	± ---	± ---

ANGULAR ± .5 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM/IN
SCALE: 2:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: SSTEINKE DATE: 2002/10/01
CHECKED BY: SFILIPON DATE: 2002/10/08
APPROVED BY: MHEIM DATE: 2002/10/08

TITLE: SHIELDED MOD. PLUG CAT.6 8 POS. WITH WIRE MANAGER ROUND CABLE

MOLEX INCORPORATED

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-85568-001
SHEET NO.: 2 OF 2
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION