

Nut Torque: 5 ~ 14Nm

Operating Pressure: 400gf ± 200gf

Operating Stroke: 1.8mm ± 0.5

Protection Grade: IP65, IK08

Function: (ON)-OFF

Contact: Silver Alloy

Base: PA66

Shell: Brass, Ni Plating

Button: SUS

Rating (Resistive load): 3A 250V AC

Contact Resistance: 50mΩ MAX.

Insulation Resistance: 100MΩ MIN.

Dielectric Strength: 1500V AC 1 minute

Electrical life: 50,000 cycles


Mechanical life: 200,000 cycles

Operating Temperature: -20°C ~ 80°C

Relative Air Humidity: 45% ~ 85%

Safety Approval:

SWITCHING CIRCUIT



**D-SWITCH**  
东莞市德兹电子有限公司  
D-SWITCH ELECTRONICS CO.,LTD.

公差 TOLERANCES .X± 0.5 .XX± 0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VERSION	A0	比例尺 SCALE	1:1	日期 DATE	2021.04.27	品名 TITLE	图号 DRAWING NO
核准 APPROVED BY		核对 CHECKED BY		绘图 DRAWN BY	孙成	PBM-16M11-FS-N-NN-B8L-A3	PBM-16M11-FS-N-NN-B8L-A3_A0

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.
--------	-------------------------	---------	---------