SAW Components

Data Sheet B7840

© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.

Data Sheet


Chip **S**ized **S**AW **P**ackage

Features

- Low loss RF filter for GPS receivers
- Unbalanced to balanced operation
- Low amplitude ripple
- Impedance transformation from 50 Ω to 100 Ω
- Package for **S**urface **M**ounted **T**echnology **(SMT)**

Terminals


- Ni, gold-plated



Dimensions 2,0x1,4 mm², approx. weight 0,007 g

Pin configuration

1	Input, unbalanced
3, 4	Output, balanced
2, 5	Case ground



Type	Ordering code	Marking and Package according to	Packing according to
B7840	B39162-B7840-C710	C61157-A7-A82	F61074-V8151-Z000

Electrostatic **S**ensitive **D**evice (**ESD**)

Maximum ratings

Operable temperature range	T	– 40/+ 85	˚C	
Storage temperature range	T_{stg}	– 40/+ 85	˚C	
DC voltage	V_{DC}	3	V	
Source power	P_s	10	dBm	824...1525, 1710...2500 MHz
source 50 Ω, load 100 Ω		5		elsewhere

Data Sheet


Characteristics


Operating temperature range: T_A = -30 ... +85 °C
Terminating source impedance: Z_S = 50 Ω unbal.
Terminating load impedance: Z_L = 100 Ω bal.

		min.	typ.	max.	
Nominal frequency	f_N	—	1575,42	—	MHz
Maximum insertion attenuation	α_{max}				
1574,42MHz ... 1576,42MHz*)		—	1,2	1,6	dB
1574,42MHz ... 1576,42 MHz		—	1,2	1,7	dB
Amplitude ripple in passband (p-p)	$\Delta\alpha$				
1574,42MHz ... 1576,42 MHz		—	0,1	0,3	dB
Output phase balance ($\phi(S_{31})-\phi(S_{21})+180°$)					
1574,42MHz ... 1576,42 MHz		-10	6	10	°
Output amplitude balance ($\lvert S_{31}/S_{21}\rvert$)					
1574,42MHz ... 1576,42 MHz		-1,0	0,2	1,0	dB
Return loss					
1574,42 ...1576,42 MHz		11,0	21	—	dB
VSWR					
1574,42 ...1576,42 MHz		—	1,2	1,8	
Absolute attenuation	α_{rel}				
100,0 MHz ... 960,0 MHz		40	48	—	dB
960,0 MHz ... 1425,0 MHz		35	42	—	dB
1425,0 MHz ... 1475,0 MHz		30	42	—	dB
1475,0 MHz ... 1515,0 MHz		20	32	—	dB
1515,0 MHz ... 1525,0 MHz		17	27	—	dB
1625,0 MHz ... 1635,0 MHz		12	30	—	dB
1635,0 MHz ... 1675,0 MHz		20	30	—	dB
1675,0 MHz ... 1750,0 MHz		30	34	—	dB
1750,0 MHz ... 1805,0 MHz		35	44	—	dB
1805,0 MHz ... 1980,0 MHz		40	47	—	dB
1980,0 MHz ... 2400,0 MHz		35	39	—	dB
2400,0 MHz ... 3155,0 MHz		40	52	—	dB
3155,0 MHz ... 6000,0 MHz		35	44	—	dB

*) T_A= +25 °C

Transfer function





Published by EPCOS AG
SAW MC WT, P.O. Box 80 17 09, 81617 Munich, GERMANY
TEL ++49 89 636 09, FAX ++49 89 636 2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.