



Circular Plug Terminal Blocks IP68
Circular Plug Connectors AC 179 kompakt
AC 179 SK/ 4 SL



Terminal Block, 4 pole, Voltage Rating: 450 V, Current Rating: 17.5 A, Cross-Section: 4.0 mm²

Order Info

Reference Number (ref. no.)	741064D3
Applications	Lighting, Installation
PU	200

Type

Type	Terminal Block
Number of poles	4 pole
Clamping Units per Pole	1
Colour	black
Cross-Section	4.0 mm ²
Connection Type	Screw

Technical Data

Voltage Rating	450 V
Current Rating	17.5 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.5 mm ²
Core Cross-Section max.	4.0 mm ²
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
IP Code	IP68
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.0 mm
Dismantling Length	20.0 mm
Assembly Contact Screw	0.5x3.0 / ⌀ 0.5 Nm
Assembly Strain Relief	⌀ 2.5 Nm
Cable Diameter min.	7.0 mm
Cable Diameter max.	12.0 mm

Accessories

AC 179 RVK/ 4 M20	749564
DR 14 1x5,5x11	729007
DR 14 1x3,5	729008
DR 14 1x7,0	729001
DR 14 2x3,0	729003
DR 14 2x5,0	729004
DR 14 3x3,0	729005
DR 14 4x3,0	729006
DR 14 RH	729002
DR 14 GS	729010