



Screwless Connectors  
Luminaire Connectors

LK 980-01/ 5 STW printed "3 N Earth 1 2"

Terminal Block, 5 pole, Fixing: Screw, PE Terminal: STW, Printing: 3 N Earth 1 2, Voltage Rating: 450 V, Current Rating: 24 A, Cross-Section: 2.5 mm<sup>2</sup>, External Connection Type: screwless



Order Info

Reference Number (ref. no.)	041415
Applications	Lighting, Electrical Appliances
PU	500

Type

Type	Terminal Block
Number of poles	5 pole
Clamping Units per Pole	2
Colour	white
Cross-Section	2.5 mm <sup>2</sup>
Printing	3 N Earth 1 2

Technical Data

Voltage Rating	450 V
Current Rating	24 A
Insulating Material	PA 6.6
Contact Material	Spring Steel, Copper
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Stripping Length	8.0-9.0 mm
Internal Core Cross-Section max.	1.5 / 2.5 mm <sup>2</sup>
External Core Cross-Section min.	0.5 mm <sup>2</sup>
External Core Cross-Section max.	2.5 mm <sup>2</sup>
Fixing	Screw
External Connection Type	screwless
Internal Core Cross-Section min.	0.5 mm <sup>2</sup>
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes

<b>PE Terminal</b>	STW
<b>Approbation EN60998</b>	LK980-01_EN60998_20070627_20101213_VDE_ENEC_40021343_v
<b>Approbation UL</b>	LK980_20010625_20110411_UL_E63492_1-18_Description_web.pdf

## Accessories

<b>WKZ 980-01</b>	999041
<b>ZEL 110</b>	196420
<b>ZEL 900</b>	196423