


Helping Customers Innovate, Improve & Grow



## Description

The TX-550 Series TCXO innovative manufacturing and the latest technology to provide extremely low phase noise and g-sensitivity. The assembly includes a dual crystal circuit to cancel opposing g-sensitivity vectors.

## Features

- Low Phase Noise, Low G-Sensitivity
- Fully RoHS Compliant 
- Surface Mount, Low Profile
- High Shock Survival up to 20K g
- Frequency Range: 8 MHz to 80 MHz

## Applications

- Military Portable Radios
- GPS Telemetry
- Test and Measurement Equipment


## Performance Specifications

Parameter	Min	Typ	Max	Units	Condition
<b>Frequency Stabilities<sup>1</sup></b>					
vs. operating temperature range (referenced to +25°C)	-2.0		+2.0	ppm	-40... +85°C
	-1.0		+1.0	ppm	-40... +85°C
	-0.5		+0.5	ppm	-20... +70°C
	-0.28		+0.28	ppm	0... +50°C
Initial Tolerance vs. supply voltage change vs. load change vs. aging / 1 year vs. aging	-1.0		+1.0	ppm	at time of shipment, nominal EFC Vs ± 5% Load ± 10% @ +40°C for 15 years
	-0.1		+0.1	ppm	
	-0.2		+0.2	ppm	
		±1		ppm	
			4.0	ppm	
<b>Supply Voltage (Vs)</b>					
Supply voltage	4.75	5.0	5.25	VDC	
Supply voltage	3.135	3.3	3.465	VDC	
Supply voltage	2.7	2.8	2.9	VDC	
Current consumption			35	mA	Depends on frequency
<b>RF Output</b>					


## Performance Specifications

Parameter	Min	Typ	Max	Units	Condition
Signal	HCMOS				
Load		15		pF	
Signal Level (Vol)			0.1*Vs	V	
Signal Level (Voh)	0.9*Vs			V	
Rise/Fall Time			5	ns	@ nominal Load and 10% to 90% of waveform
Duty cycle	40	50	60	%	@ nominal Load and @ 50% level
Signal	Clipped Sinewave				
Level		1		Vpp	with Nominal Load
Load R		10		kohm	
Load C		10		pF	
<b>Frequency Tuning (EFC)</b>					
Tuning Range	Fixed; No adjust				
Tuning Range	±5.0			ppm	
Tuning Slope	Positive				
Control Voltage Range	0.0		Vs	VDC	
Freq. control input impedance	10			kohm	
<b>Additional Parameters<sup>1</sup></b>					
Phase Noise <sup>3</sup> (@ 20 MHz - no vibration)		-90 -120 -140 -145 -150		dBc/Hz dBc/Hz dBc/Hz dBc/Hz dBc/Hz	10 Hz 100 Hz 1 kHz 10 kHz 100 kHz
G-Sensitivity		0.2		ppb/g	per axis
Shock					MIL-STD-202G; Method 213B; Test Condition B
Vibration Random					MIL-STD-202G; Method 214A; Test Condition I-F
Vibration Sine					MIL-STD-202G, METHOD 204D, Test Condition A
Thermal Cycling					MIL-STD-202, METHOD 107, Test Condition A
<b>Absolute Maximum Ratings</b>					
Supply voltage (Vs)			6.0	V	Damage will occur beyond this level
Control Voltage	0		Vs	V	
Operable temperature range	-45		+90	°C	
Storage temperature range	-55		+105	°C	

# PhaseNoise Plot:




## Standard Shipping Method




## Production tolerance complying DIN IEC 286-3

Enclosure Type	Tape width W (mm)	Quantity per meter	Quantity per reel	Dimension P

## Recommended Reflow Profile



# Outline Drawing / Enclosure




PIN NUMBERS SHOWN FOR REFERENCE ONLY

Dimensions in inches (mm)

TX-550 Pin Connections	
1	Electronic Frequency Control (EFC)
2	Ground
3	RF Output
4	Supply

## Ordering Information



### Notes:

1. Contact factory for improved stabilities or additional product options. Not all options and codes are available at all frequencies.
2. Unless other stated all values are valid after warm-up time and refer to typical conditions for supply voltage, frequency control voltage, load, temperature (25°C).
3. Phase noise degrades with increasing output frequency.
4. Subject to technical modification.
5. Contact factory for availability.

## For Additional Information, Please Contact

### USA:

Vectron International  
267 Lowell Road, Suite 102  
Hudson, NH 03051  
Tel: 1.888.328.7661  
Fax: 1.888.329.8328

### Europe:

Vectron International  
Landstrasse, D-74924  
Neckarbischofsheim, Germany  
Tel: +49 (0) 3328.4784.17  
Fax: +49 (0) 3328.4784.30

### Asia:

Vectron International  
68 Yin Cheng Road(C), 22nd Floor  
One LuJiaZui  
Pudong, Shanghai 200120, China  
Tel: +86 21 6194 6886  
Fax: +86 21 6194 6699

### Disclaimer

Vectron International reserves the right to make changes to the product(s) and or information contained herein without notice. No liability is assumed as a result of their use or application.  
No rights under any patent accompany the sale of any such product(s) or information.

2-18-2014 jar