ADELS contact

Fused Connectors

1003 Si/ 3 E DS GW



Screw Terminal Block mit PE Terminal am Blech, 3 pole, Wire Protector (DS): yes, Cross-Section: 4.0 mm², Voltage Rating: 500 V, Current Rating: 16 A

Order Info

Reference Number (ref. no.)	1717G3
Applications	Lighting, Electrical Appliances, Transformers
PU	0

Type

Type	Screw Terminal Block mit PE Terminal am Blech
Number of poles	3 pole
Clamping Units per Pole	1
Colour	natural
Cross-Section	4.0 mm²
Connection Type	Screw
Wire Protector (DS)	yes

Technical Data

Voltage Rating	500 V
Current Rating	16 A
Insulating Material	PA 6.6-GW
Contact Material	Brass
Core Cross-Section min.	0.5 mm²
Core Cross-Section max.	4.0 mm²
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	7.5-8.0 mm
Assembly Contact Screw	0.8x4.0 / ↻ 0.8 Nm
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes

Type of Conductor Flexible Internal	yes

Accessories

ZEL 110	196420