

SOT-23 Plastic-Encapsulate Transistors

BCW68 TRANSISTOR (PNP)

FEATURES


Complementary to BCW66, BCW68 is subdivided into three groups F, G and H according to its DC current gain.

MAXIMUM RATINGS (T_a=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V _{CBO}	Collector-Base Voltage	-60	V
V _{CEO}	Collector-Emitter Voltage	-45	V
V _{EBO}	Emitter-Base Voltage	-5	V
I _C	Collector Current	-800	mA
P _C	Collector Power Dissipation	330	mW
R _{θJA}	Thermal Resistance From Junction To Ambient	379	°C/W
T _J , T _{stg}	Operation Junction and Storage Temperature Range	-55~+150	°C

SOT-23

1. BASE
2. EMITTER
3. COLLECTOR










ELECTRICAL CHARACTERISTICS (T_a=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	V _{(BR)CBO}	I _C =-10 μA, I _E =0	-60			V
Collector-emitter breakdown voltage	V _{(BR)CEO}	I _C =-10mA, I _B =0	-45			V
Emitter-base breakdown voltage	V _{(BR)EBO}	I _E =-10 μA, I _C =0	-5			V
Collector cut-off current	I _{CBO}	V _{CB} =-45 V, I _E =0			-0.02	μA
Collector cut-off current	I _{EBO}	V _{EB} =-4 V, I _C =0			-0.02	μA
DC current gain	h _{FE1}	V _{CE} =-10V, I _C =-0.1mA F G H	35 50 80			
	h _{FE2}	V _{CE} =-1V, I _C =-10mA F G H	75 120 180			
	h _{FE3}	V _{CE} =-1V, I _C =-100mA F G H	100 160 250		250 400 630	
	h _{FE4}	V _{CE} =-2V, I _C =-500mA F G H	35 60 100			
Collector-emitter saturation voltage	V _{CE(sat)}	I _C =-100mA, I _B =-10mA			-0.3	V
		I _C =-500mA, I _B =-50mA			-0.7	V
Base-emitter saturation voltage	V _{BE(sat)}	I _C =-100mA, I _B =-10mA			-1.25	V
		I _C =-500mA, I _B =-50mA			-2	V
Transition frequency	f _T	V _{CE} =-5V, I _C =-50mA, f=20MHz		200		MHz
Output capacitance	C _{ob}	V _{CB} =-10V, I _E =0, f=1MHz		6		pF
Input capacitance	C _{ib}	V _{EB} =-0.5V, I _E =0, f=1MHz		60		pF


MARKING

Rank	F	G	H
Range	100-250	160-400	250-630
Marking	DF	DG	DH

Typical Characteristics



SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



- Note:
1. Controlling dimension: in millimeters.
 2. General tolerance: $\pm 0.05\text{mm}$.
 3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

SOT-23 Embossed Carrier Tape




Packaging Description:
SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	