



Circular Plug Terminal Blocks IP68 Circular Plug Connectors AC 179 kompakt AC 179 SKE/ 4 SL M25 LWD

Panel Mount Terminal Block längswasserdicht, 4 pole, Voltage Rating: 450 V, Current Rating: 17.5 A, Cross-Section: 4.0 mm², Housing Hole Diameter: M25



Order Info

Reference Number (ref. no.)	74064WS
Applications	Lighting, Installation
PU	0

Type

Type	Panel Mount Terminal Block längswasserdicht
Number of poles	4 pole
Clamping Units per Pole	1
Colour	black
Cross-Section	4.0 mm ²
Connection Type	Screw

Technical Data

Voltage Rating	450 V
Current Rating	17.5 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.75 mm ²
Core Cross-Section max.	4.0 mm ²
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
IP Code	IP68
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.0 mm
Dismantling Length	20.0 mm
Assembly Contact Screw	0.5x3.0 / ⚙ 0.5 Nm
Assembly Strain Relief	⚙ 2.5 Nm
Cable Diameter min.	7.0 mm
Cable Diameter max.	12.0 mm

Housing Hole Diameter	M25
-----------------------	-----

Accessories

AC 179 RVK/ 4 M20	749564
DR 14 1x5,5x11	729007
DR 14 1x3,5	729008
DR 14 1x7,0	729001
DR 14 2x3,0	729003
DR 14 2x5,0	729004
DR 14 3x3,0	729005
DR 14 4x3,0	729006
DR 14 RH	729002
DR 14 GS	729010