Product data sheet
Characteristics

QOB130VH1200
Mini CB, QO, 30 A, 1P, 120/240 V, 22 kA, Bolt on, Aux Switch 1A

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	30 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	1P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Pressure plate
Options	Auxiliary switch 120 V AC 1A

Complementary

Inturrupt Rating	22 kA 120/240 V AC 50/60 Hz 22 kA 120 V AC 50/60 Hz
Number of Panel Spaces	2
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening torque	44.25 lbf.in (5 N.m) 0.02…0.04 in² (10…25 mm²) AWG 8...AWG 2)
Height	76.20 mm (3 in)
Depth	73.91 mm (2.91 in)
Width	38.10 mm (1.5 in)

Environment

Certifications	UL listed CSA
Ambient Rating	104 °F (40 °C)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Package weight(Lbs)	4.80 oz (136.078 g)

Offer Sustainability

EU RoHS Directive	Under investigation