




FCS-3083 Version: 1

! Power supply unit is to be ordered separately.

Varifocal Dome IP Network Camera, 5-Megapixel, 802.3af PoE, IR LEDs, Vandalproof, Indoor/Outdoor, two-way audio



Key Features

- 2.8-12 mm adjustable Vari-focal length for wide angle surveillance
- 5-Megapixel high-definition resolution
- Weatherproof IP67-rated housing
- Built-in Micro SDHC/SDXC card slot for local storage
-
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Vandal-proof IK10-rated housing
- Built-in infrared LEDs for night viewing up to 30m
- Removable IR-cut filter for day and night surveillance
- Video compression: H.264, MJPEG
- Power support: PoE (IEEE 802.3af)
- Free surveillance and CMS (Central Management System) software packages with 64-channel license



Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
IEEE 802.3u 100-BASE-TX, Fast Ethernet
IEEE 802.3af Power over Ethernet (PoE)
IEEE 802.1X Network Access Control
TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

Image Sensor:

5-Megapixel 1/3.2" Progressive Scan CMOS

Lens:

Vari-focal, Fixed iris, Manual focus, f2.8-12 mm, F1.4

Port:

1 x RJ-45 10/100 Mbps PoE port
1 x 3.5mm line out
1 x 3.5mm line in
I/O terminal block (1 DI/1 DO)
1 x MicroSDHC/ MicroSDXC card slot

Button/Knob:

Reset Button

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

15 IR LEDs for illumination up to 30m

Shutter Time:

1/5 ~ 1/10,000 sec

Angle of View:

69.2° - 28.2°

Pan/Tilt/Zoom:

Digital Zoom to very high detail available on Software

Video Compression:

H.264 / MJPEG

Resolution:

5M(2592 x 1944)

Output Video Format:

RAW

Audio Compression:

G.711

Power Input:

802.3af PoE

Power Consumption:

PoE Class 2 (IEEE802.3af) / 6.49 W (IR on)

Data Rate:

10/100Mbps

Storage Capacity:
SD/MicroSD memory card of up to 64GB

Features

General:

Backup: MicroSDHC /MicroSDXC card slot for local storage

Video:

Image Setting: - Adjustable image size, quality and bit rate
- Configurable brightness, sharpness, contrast, saturation, white balance and exposure
- AGC/AWB/AES
- Back Light Compensation (BLC)
- Wide Dynamic Range (WDR), Basic WDR (74 dB)
- 2D Noise Reduction (2DNR)
Streaming: Up to 2 video streams

Audio:

Streaming: 2-way audio
Input/Output: line input, line output

Performance

Frame Rate (fps):

15 fps at 2592 x 1944; 15 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

Minimum illumination:

Color: 0.1 lux at F1.4
B/W: 0 lux (IR LED on)

Environment

Operating Temperature (°C):

Operating: -40°C ~ 50°C

Operating Humidity (Non-condensing):

Operating: 10% ~ 85%

Installation:

Ceiling Mount

Physical Specifications

Dimensions (W x D x H mm):

150 x 117 x 150

Weight (g):

1032 g

Approval and Compliance

EMI/EMS:

CE, RoHS, FCC, ONVIF, IK10, NEMA 4X

Environmental Test:

Weather proof IP67-rated housing
Vandal proof IK10-rated


Others

Supported Browsers:

Microsoft Windows 8/7/Vista/XP



Diagram



Order Information

FCS-3083

Package Contents

FCS-3083
Screw Kit
Quick Installation Guide
Resource CD (User Manual, Utility, QIG)

Optional Accessory



CAS-2101
Pendant Cap



CAS-2102
Pendant Mount Bracket



CAS-2103
Pendant Mount Bracket



CAS-2104
Extension Tube



CAS-2314
Wall Mount Bracket



CAS-2402
Corner Mount Bracket



CAS-2503
Pole Mount Bracket, Clamping Range 5.25"-8.5"



CAS-3001
Flush Mount Bracket