



43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High Power High Gain Amplifier, 48 dBm IP3, SMA

TECHNICAL DATA SHEET

PE15A5028

The PE15A5028 is a 25W high gain coaxial power amplifier operating in the 0.15 to 230 MHz frequency range. The amplifier offers 25 Watts typical saturated power and 43 dB minimum small signal gain with ± 1.5 dB maximum of gain flatness. The amplifier requires typically a +28V DC power supply. The connectorized SMA module is unconditionally stable and operates over the temperature range of 0°C and +50°C.

Features

- 0.15 MHz to 230 MHz Frequency Range
- Psat 25 Watts typ
- Small Signal Gain: 43 dB min
- Gain Flatness ± 1.5 dB max
- IP3 48 dBm typ
- 50 Ohms Input and Output Matched
- Unconditionally Stable
- Regulated Supply

Applications

- Military Radio
- Communication Systems
- High Gain Driver Power Amplifier
- High Gain Output Power Amplifier

Electrical Specifications (TA = +25°C, DC Voltage = 28Volts, DC Current = 5,000mA)

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.15		230	MHz
Small Signal Gain	43			dB
Gain Flatness			± 1.5	dB
Input Power			+1	dBm
Psat		+44		dBm
Output Power at 1 dB Compression Point	+41.8			dBm
Output 3rd Order Intercept Point		+48		dBm
Harmonics		-15		dBc
Spurious		-60		dBc
Input VSWR			2:1	
TTL Control		"1" = On; "0" = Off		
TTL Control Enable		5		Volts
TTL Control Disable		0		Volts
Operating DC Voltage		28		Volts
Operating DC Current			5,000	mA
Operating Temperature Range	0		+50	°C

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High Power High Gain Amplifier, 48 dBm IP3, SMA PE15A5028](#)



43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High
Power High Gain Amplifier, 48 dBm IP3, SMA

TECHNICAL DATA SHEET

PE15A5028

Mechanical Specifications

Size

Length	6 in [152.4 mm]
Width	3 in [76.2 mm]
Height	1.1 in [27.94 mm]
Weight	1.5 lbs [680.39 g]
Input Connector	SMA Female
Output Connector	SMA Female
Cooling	ADEQUATE HEATSINK REQUIRED

Environmental Specifications

Temperature

Operating Range	0 to +50 deg C
Humidity	95% Non-Condensing
Shock	Normal Truck Transport
Vibration	Normal Truck Transport
Altitude	10000 feet Above Sea Level

Compliance Certifications (visit www.Pasternack.com for current document)

Not RoHS Compliant

Plotted and Other Data

Notes:

- Values at +25 °C, sea level
- ESD Sensitive Material, Transport material in Approved ESD bags. Handle only in approved ESD Workstation.
- Heat Sink Required for Proper Operation, Unit is cooled by conduction to heat sink.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High Power High Gain Amplifier, 48 dBm IP3, SMA PE15A5028](#)





43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High Power High Gain Amplifier, 48 dBm IP3, SMA

TECHNICAL DATA SHEET

PE15A5028

Typical Performance Data





Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High Power High Gain Amplifier, 48 dBm IP3, SMA PE15A5028](#)



43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High Power High Gain Amplifier, 48 dBm IP3, SMA

TECHNICAL DATA SHEET

PE15A5028



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High Power High Gain Amplifier, 48 dBm IP3, SMA PE15A5028](#)



43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High
Power High Gain Amplifier, 48 dBm IP3, SMA

TECHNICAL DATA SHEET

PE15A5028

43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High Power High Gain Amplifier, 48 dBm IP3, SMA from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High Power High Gain Amplifier, 48 dBm IP3, SMA PE15A5028](http://www.pasternack.com/43-db-gain-230-mhz-high-power-high-gain-amplifier-ip3-sma-pe15a5028-p.aspx)

URL: <http://www.pasternack.com/43-db-gain-230-mhz-high-power-high-gain-amplifier-ip3-sma-pe15a5028-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE15A5028 CAD Drawing

43 dB Gain, 25 Watt Psat, 0.15 MHz to 230 MHz, High
Power High Gain Amplifier, 48 dBm IP3, SMA



NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE

PE15A5028

FSCM NO. 53919

CAD FILE 010615

SCALE N/A

SIZE A

150

PE PASTERNAK
THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com