

HCD6NC70S

700V N-Channel Super Junction MOSFET

FEATURES

- ❑ Originative New Design
- ❑ Superior Avalanche Rugged Technology
- ❑ Robust Gate Oxide Technology
- ❑ Very Low Intrinsic Capacitances
- ❑ Excellent Switching Characteristics
- ❑ Unrivalled Gate Charge : 7 nC (Typ.)
- ❑ Extended Safe Operating Area
- ❑ Lower $R_{DS(ON)}$: 1.05 Ω (Typ.) @ $V_{GS}=10V$
- ❑ 100% Avalanche Tested

$$BV_{DSS} = 700 V$$


$$R_{DS(on) typ} = 1.05 \Omega$$

$$I_D = 5.0 A$$

D-PAK



1.Gate 2. Drain 3. Source



Absolute Maximum Ratings $T_C=25^\circ C$ unless otherwise specified

Symbol	Parameter		Value	Units
V_{DSS}	Drain-Source Voltage		700	V
I_D	Drain Current	– Continuous ($T_C = 25^\circ C$)	5.0	A
	Drain Current	– Continuous ($T_C = 100^\circ C$)	3.2	A
I_{DM}	Drain Current	– Pulsed (Note 1)	13.0	A
V_{GS}	Gate-Source Voltage	Static	± 20	V
		AC ($f > 1$ Hz)	± 30	V
E_{AS}	Single Pulsed Avalanche Energy	(Note 2)	25	mJ
I_{AR}	Avalanche Current	(Note 1)	1.0	A
E_{AR}	Repetitive Avalanche Energy	(Note 1)	0.1	mJ
dv/dt	Peak Diode Recovery dv/dt	(Note 3)	50	V/ns
P_D	Power Dissipation ($T_A = 25^\circ C$)*		2.1	W
	Power Dissipation ($T_C = 25^\circ C$)		28	W
T_J, T_{STG}	Operating and Storage Temperature Range		-55 to +150	$^\circ C$
T_L	Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds		300	$^\circ C$

Thermal Resistance Characteristics

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case	--	4.4	$^\circ C/W$
$R_{\theta JA}$	Junction-to-Ambient*	--	60.5	
T_{sold}	Soldering temperature, wave soldering only allowed at leads	--	260	$^\circ C$

* When mounted on the minimum pad size recommended (PCB Mount)

Package Marking and Odering Information

Device Marking	Week Marking	Package	Packing	Quantity	RoHS Status
HCD6NC70S	YWWX	TO-251	Tube / Reel	80 / 2,500	Pb Free
HCD6NC70S	YWWXg	TO-251	Tube / Reel	80 / 2,500	Halogen Free

Electrical Characteristics $T_J=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
--------	-----------	-----------------	-----	-----	-----	-------

On Characteristics

V_{GS}	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$	2.5	--	4.5	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS} = 10\ \text{V}, I_D = 1.5\ \text{A}$	--	1.05	1.25	Ω

Off Characteristics

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0\ \text{V}, I_D = 250\ \mu\text{A}$	700	--	--	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 700\ \text{V}, V_{GS} = 0\ \text{V}$	--	--	1	μA
		$V_{DS} = 560\ \text{V}, T_J = 125^\circ\text{C}$	--	--	10	μA
I_{GSS}	Gate-Body Leakage Current	$V_{GS} = \pm 20\ \text{V}, V_{DS} = 0\ \text{V}$	--	--	± 100	nA

Dynamic Characteristics

C_{iss}	Input Capacitance	$V_{DS} = 100\ \text{V}, V_{GS} = 0\ \text{V},$ $f = 1.0\ \text{MHz}$	--	300	390	pF
C_{oss}	Output Capacitance		--	20	26	pF
C_{rss}	Reverse Transfer Capacitance		--	5	6.5	pF

Switching Characteristics

$t_{d(on)}$	Turn-On Time	$V_{DS} = 350\ \text{V}, I_D = 1.5\ \text{A},$ $R_G = 10\ \Omega$ (Note 4,5)	--	15	40	ns
t_r	Turn-On Rise Time		--	20	50	ns
$t_{d(off)}$	Turn-Off Delay Time		--	50	110	ns
t_f	Turn-Off Fall Time		--	25	60	ns
Q_g	Total Gate Charge	$V_{DS} = 560\ \text{V}, I_D = 1.5\ \text{A}$ $V_{GS} = 10\ \text{V}$ (Note 4,5)	--	7.0	9.0	nC
Q_{gs}	Gate-Source Charge		--	1.5	--	nC
Q_{gd}	Gate-Drain Charge		--	2.0	--	nC
$V_{plateau}$	Gate-Plateau Voltage		--	5.0	--	V

Source-Drain Diode Maximum Ratings and Characteristics

I _S	Continuous Source-Drain Diode Forward Current		--	--	5.0	A
I _{SM}	Pulsed Source-Drain Diode Forward Current		--	--	13.0	
V _{SD}	Source-Drain Diode Forward Voltage	I _S = 1.5 A, V _{GS} = 0 V	--	--	1.2	V
t _{rr}	Reverse Recovery Time	I _S = 1.5 A, V _{GS} = 0 V di _F /dt = 100 A/μs (Note 4)	--	120	--	ns
Q _{rr}	Reverse Recovery Charge		--	1	--	μC
I _{rrm}	Peak Reverse Recovery Current		--	9	--	A

Notes ;

1. Repetitive Rating : Pulse width limited by maximum junction temperature
2. $L=15\text{mH}, I_{AS}=2\text{A}, V_{DD}=50\text{V}, R_G=25\Omega$, Starting $T_J=25^\circ\text{C}$
3. $I_{SD}\leq 5.0\text{A}, di/dt\leq 200\text{A}/\mu\text{s}, V_{DD}\leq BV_{DSS}$, Starting $T_J=25^\circ\text{C}$
4. Pulse Test : Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$
5. Essentially Independent of Operating Temperature

Typical Characteristics




Figure 1. On Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On Resistance Variation vs Drain Current and Gate Voltage




Figure 4. Body Diode Forward Voltage Variation with Source Current and Temperature




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge Characteristics

Typical Characteristics (continued)




Figure 7. Breakdown Voltage Variation vs Temperature




Figure 8. On-Resistance Variation vs Temperature




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs Case Temperature





Figure 11. Transient Thermal Response Curve

Fig 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms



Package Dimension

TO-252

