


Sales Region	USA/China/ASEAN/India
Series	PHV
Model	
Status	 Production
Option	
Option Lineup	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input	Single-phase
Input Voltage Range[AC]	104 to 126VAC
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	200Vdc
Output Voltage Range[DC]	0 to 200V
Rated Output Current	3A
Output Current	0 to 3000mA
Rated Output Power	700W
Polarity	Floating
Power Factor	0.72
Efficiency	90% Typ.
Voltage Ripple Noise	240mV

Package Type & Size

Package / Mounting	Rack mount
Width(W)	443mm Nom. (17.44in Nom.)
Height(H)	133mm Nom. (5.24in Nom.)
Depth(D)	350mm Nom. (13.78in Nom.)
Weight	9000g Typ. (19.8lbs Typ.)

Other

Operating Temp. Range	0 to 40°C
Storage Temp. Range	0 to 40°C
Cooling	Forced air
Safety Standard(Certified)	
Safety Standard(Conformed)	EN61010-1 CE Mark
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.