

Ferrule - A 70 -40 - 3241241

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Ferrule, length: 40 mm, color: silver

Your advantages

- The ferrules without plastic sleeve are made from soft tin-plated electrolytic copper



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 100 pc |
| GTIN |  4 046356 908146 |
| GTIN | 4046356908146 |

Technical data

Dimensions

| | |
|--|---------|
| Length (b) | 40 mm |
| Maximum stripping length | 40 mm |
| Inner dimension of the insulating collar (d) | 15 mm |
| Ferrule diameter | 12.5 mm |
| Sleeve wall thickness | 0.4 mm |

Ambient conditions

| | |
|----------------------------|--------|
| Short-term temperature | 120 °C |
| Max. permanent temperature | 105 °C |

General

| | |
|----------|---|
| Note | These ferrules are not included in DIN 46228-1: 1992-08 |
| Color | silver |
| Material | CU-DHP |
| Coating | tin-plated (galvanic) |

Environmental Product Compliance

Ferrule - A 70 -40 - 3241241

Technical data

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>