



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer LCP、PA6T、UL94V-0
PIN Brass Tin-plated
Solder tad Phosphoric bronze Tin-plated

| 编 号 | 尺寸 (mm) | | |
|-------------|---------|-------|-------|
| | A | B | C |
| HC-HA-2ALT | 2.50 | 10.00 | 7.50 |
| HC-HA-3ALT | 5.00 | 12.50 | 10.00 |
| HC-HA-4ALT | 7.50 | 15.00 | 12.50 |
| HC-HA-5ALT | 10.00 | 17.50 | 15.00 |
| HC-HA-6ALT | 12.50 | 20.00 | 17.50 |
| HC-HA-7ALT | 15.00 | 22.50 | 20.00 |
| HC-HA-8ALT | 17.50 | 25.00 | 22.50 |
| HC-HA-9ALT | 20.00 | 27.50 | 25.00 |
| HC-HA-10ALT | 22.50 | 30.00 | 27.50 |
| HC-HA-11ALT | 25.00 | 32.50 | 30.00 |
| HC-HA-12ALT | 27.50 | 35.00 | 32.50 |

| | | | | | | | | |
|-------------------|------------|------------------------------|-----------------|---------------------|------------------------|---------------------------|--------------|-----|
| GENERAL TOLERANCE | | 制 图 DRAWING 2017、06、01 | 料 号 PART NO. | HC-HA-NALT | | 版 本 REV. | A | |
| X.±0.25 | X.*±2' | | 审 核 CHECK | 品 名 TITLE | HA立贴 WAFER SMT TYPE | | 页 次 SHEET | 1/1 |
| .X±0.20 | .X*±1' | | 核 准 APPROVAL | 客 户 料 号 CUTL NO. | | | | |
| .XX±0.15 | .XX*±0.5' | | 单 位 UNITS | 2017、06、05 | | 深 圳 市 华 灿 天 禄 电 子 有 限 公 司 | | |
| .XXX±0.10 | .XXX*±0.5' | MM | 比 例 SCALE | 1:1 | | | | |