
IC0603A102R-10

UNCONTROLLED DOCUMENT

PHYSICAL DIMENSIONS:

A	1.60 [.063]	± 0.15[.006]
B	0.80 [.031]	± 0.15[.006]
C	0.80 [.031]	± 0.15[.006]
D	0.30 [.012]	± 0.20[.008]




Pb

NOTES: UNLESS OTHERWISE SPECIFIED
1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 4000 PCS/REEL, PAPER TAPE.
2. TERMINATION FINISH IS 100% MATTE Sn OVER Ni.
3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
4. I (MAX.) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MAXIMUM TEMPERATURE RISE OF 40°C OVER AMBIENT.
5. I (OPERATING) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MINIMUM INDUCTANCE (L).
6. OPERATING TEMP. RANGE: −40°C~+125°C. (INCLUDING SELF−HEATING)

ELECTRICAL CHARACTERISTICS:


L (nH) ± 10%	1,100	Max
	1,000	Nom
	900	Min@ 25mA
Q (Min)	30	
Freq. (MHz)	10	
Self−Resonant Freq (MHz)	70	
DCR(Max) Ω	0.60	
I (Max)	150mA	
I (Operating)	25mA	

LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762[.030] to this dimension)

RECOMMENDED SOLDERING CONDITIONS



RoHS 2002/95/EC

REV	DESCRIPTION	DATE	INT
C	ADD OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE	08/05/13	QU
B	UPDATD COMPANY LOGO	03/25/08	JRK
A	ORIGINAL DRAFT	12/22/06	JRK

DIMENSIONS ARE IN mm [INCHES].

This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.

Laird

PROJECT/PART NUMBER:	REV	PART TYPE:	DRAWN BY:
IC0603A102R−10	C	CO−FIRE	JRK

DATE:	SCALE:	SHEET:
12/22/06	NTS	2 of 2

CAD # IC0603A102R−10−C

TOOL # −