
TOSHIBA RECTIFIER SILICON DIFFUSED TYPE

U05GH44,U05JH44

HIGH SPEED RECTIFIER APPLICATIONS
(FAST RECOVERY)

- Repetitive Peak Reverse Voltage: V_{RRM} = 400, 600V
- Average Forward Current: $I_{F\ (AV)}$ = 0.5A
- Reverse Recovery Time: t_{rr} = 1.5μs
- Surface Mounting Plastic Mold Package

Unit: mm



JEDEC	—
JEITA	—
TOSHIBA	3-4D1A

Weight: 0.06 g (typ.)

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Repetitive Peak Reverse Voltage	U05GH44	V_{RRM}	400	V
	U05JH44		600	
Average Forward Current		$I_{F\ (AV)}$	0.5	A
Peak One Cycle Surge Forward Current (Non−Repetitive)		I_{FSM}	20 ($50H_Z$)	A
Junction Temperature Range		T_j	−40~125	°C
Storage Temperature Range		T_{stg}	−40~125	°C

ELECTRICAL CHARACTERISTICS (Ta = 25°C)


CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN	TYP.	MAX	UNIT
Peak Forward Voltage	V_{FM}	I_{FM} = 0.5A	—	—	1.2	V
Repetitive Peak Reverse Current	I_{RRM}	V_{RRM} = Rated	—	—	10	μA
Reverse Recovery Time	t_{rr}	I_F = 20mA, I_R = 1mA	—	—	1.5	μs

MARKING

Abbreviation Code	Part No.
GH	U05GH44
JH	U05JH44

STANDARD SOLDERING PAD

Unit : mm



Handling Precaution

The maximum ratings denote the absolute maximum ratings, which are rated values and must not be exceeded during operation, even for an instant. The following are the general derating methods that we recommend when you design a circuit with a device.

V_{RRM}: We recommend that the worst case voltage, including surge voltage, be no greater than 80% of the maximum rating of V_{RRM} for a DC circuit and be no greater than 50% of that of V_{RRM} for an AC circuit. V_{RRM} has a temperature coefficient of 0.1%/°C. Take this temperature coefficient into account designing a device at low temperature.

$I_{F(AV)}$: We recommend that the worst case current be no greater than 80% of the maximum rating of $I_{F(AV)}$. Carry out adequate heat design. If you can't design a circuit with excellent heat radiation, set the margin by using an allowable Tamax-$I_{F(AV)}$ curve.


This rating specifies the non-repetitive peak current in one cycle of a 50-Hz sine wave, condition angle 180. Therefore, this is only applied for an abnormal operation, which seldom occurs during the lifespan of the device.

We recommend that a device be used at a Tj of below 100°C under the worst load and heat radiation conditions.


Thermal resistance between junction and ambient fluctuates depending on the device's mounting condition. When using a device, design a circuit board and a soldering land size to match the appropriate thermal resistance value.

Please refer to the Rectifiers databook for further information.


$i_F - v_F$




$P_{F(AV)} - I_{F(AV)}$




Ta MAX. – $I_{F(AV)}$



$r_{th(j-a)} - t$



SURGE FORWARD CURRENT (NON-REPETITIVE)



RESTRICTIONS ON PRODUCT USE

030619EAA

- The information contained herein is subject to change without notice.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
  In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the “Handling Guide for Semiconductor Devices,” or “TOSHIBA Semiconductor Reliability Handbook” etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury (“Unintended Usage”). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer’s own risk.
- TOSHIBA products should not be embedded to the downstream products which are prohibited to be produced and sold, under any law and regulations.