

LED Indicators


3mm Prominent or Recessed




A range of panel mounting LED indicators in high quality bright chrome or black chrome plated brass housings. Fitted with fixing nut and washer.

Bezel = 4 x 7 diameter (prominent), 3 x 7 diameter (recessed). Total L behind bezel = 11.5 (prominent) 13.0 (recessed). Mounting hole diameter = 6. Shorter lead Cathode.


Drawing Number - A




Drawing Number - B



Drawing Number - C



Drawing Number - D



Dimensions : Millimetres



LED Indicators

3mm Prominent or Recessed



Specifications

Colour	Typical Lumination Intensity (mcd) at $I_F = 20\text{mA}$	V_F (typical) (V)	I_F (maximum) (mA)	Refer Drawing	Part Number
HE Red	17.5	2.0-2.6	45	A	MC19020003
Green	27.0				MC19020001
Yellow	32.0				MC19020002
HE Red	15.0	2.0-2.6	45	B	MC19030003
Green	34.0				MC19030001
Yellow	28.0				MC19030002
Pure Orange	15.0		30		MC19030008
Blue	6.0	3.8-4.4	50		MC19030007
HE Red	17.5	2.0-2.6	45	A	MC19021003
Green	27.0				MC19021001
Yellow	32.0				MC19021002
Pure Orange	17.5		30		MC19021008
Blue	5.0	3.8-4.4	50		MC19021007
HE Red	15.0	2.0-2.6	45	B	MC19031003
Green	34.0				MC19031001
Yellow	28.0				MC19031002
Pure Orange	15.0		30		MC19031008

Bezel = 5.0 x 9.5 diameter (prominent), 3.0 x 9.5 (recessed). Total L behind bezel = 12.0 (prominent), 15.0 (recessed).

Mounting hole diameter = 8.0, Shorter lead cathode.



LED Indicators

3mm Prominent or Recessed



Specifications

Colour	Typical Lumination Intensity (mcd) at I _F = 20mA	V _F (typical) (V)	I _F (maximum) (mA)	Refer Drawing	Part Number	
HE Red	20.0	2.0-2.6	45	C	MC19040003	
Green	25.0				30	MC19040001
Yellow						MC19040002
Pure Orange	20.0		50		MC19040008	
Blue	6.0		3.8-4.4		MC19040007	
HE Red	27.0	2.0-2.6	45	D	MC19050003	
Yellow	27.0				30	MC19050002
Pure Orange			50			MC19050008
Blue	7.0		3.8-4.4		MC1905007	
HE Red	20.0	2.0-2.6	45	C	MC19041003	
Green	25.0				50	MC19041001
Yellow						MC19041002
Blue	6.0				3.8-4.4	MC19041007
HE Red	27.0	2.0-2.6	45	D	MC19051003	
Green	30.0				MC19051001	
Yellow	27.0				MC19051002	
Blue	7.0				3.8-4.4	MC19051007

Operating temperature (T_{OP}) : -55°C to +70°C.

Storage temperature (T_{STG}) : -55°C to +100°C.

The Led indicator is available in bright or black chrome reflector. The 7th digit has to be coded with 0 or 1.

Bright chrome = 0

Black chrome = 1

Example : MC19020001 green with bright chrome.
MC19021000 green with black chrome.



LED Indicators

3mm Prominent or Recessed



Notes:

International Sales Offices:

	AUSTRALIA – Farnell Tel No: ++61 1300 361 005 Fax No: ++61 1300 361 225		FINLAND – Farnell Tel No: ++358 9 560 7780 Fax No: ++358 9 345 5411		ITALY – Farnell Tel No: ++39 02 93 995 200 Fax No: ++39 02 93 995 300		SPAIN – Farnell Tel No: 901 20 20 80 Fax No: 901 20 20 90
	AUSTRIA – Farnell Tel No: ++43 662 2180 680 Fax No: ++43 662 2180 670		FRANCE – Farnell Tel No: ++33 474 68 99 99 Fax No: ++33 474 68 99 90		MALAYSIA – Farnell-Newark Tel No: ++60 3 7873 8000 Fax No: ++60 3 7873 7000		SWEDEN – Farnell Tel No: ++46 8 730 50 00 Fax No: ++46 8 83 52 62
	BELGIUM – Farnell Tel No: ++32 3 475 2810 Fax No: ++32 3 227 3648		GERMANY – Farnell Tel No: ++49 89 61 39 39 39 Fax No: ++49 89 613 59 01		NETHERLANDS – Farnell Tel No: ++31 30 241 7373 Fax No: ++31 30 241 7333		SWITZERLAND – Farnell Tel No: ++44 204 64 64 Fax No: ++44 204 64 54
	BRAZIL – Farnell-Newark Tel No: ++55 11 4066 9400 Fax No: ++55 11 4066 9410		HONG KONG – Farnell-Newark Tel No: ++852 2268 9888 Fax No: ++852 2268 9899		NEW ZEALAND – Farnell Tel No: 0800 90 80 80 Fax No: 0800 90 80 81		UK – Farnell Tel No: ++44 8701 200 200 Fax No: ++44 8701 200 201
	CHINA – Farnell-Newark Tel No: ++86 10 6238 5152 Fax No: ++86 10 6238 5022		HUNGARY – Farnell Tel No: ++44 870 1200 208 Fax No: ++44 870 1200 209		NORWAY – Farnell Tel No: 800 146 70 Fax No: 800 146 76		UK – CPC ++44 8701 202 530 ++44 8701 202 531
	CZECH REPUBLIC – Farnell Tel No: ++44 870 1200 208 Fax No: ++44 870 1200 209		INDIA – Farnell Tel No: ++44 870 1200 208 Fax No: ++44 870 1200 209		PORTUGAL – Farnell Tel No: ++34 93 475 8804 Fax No: ++34 93 474 5288		USA – Newark Tel No: 800 463 9275
	DENMARK – Farnell Tel No: ++45 44 53 66 44 Fax No: ++45 44 53 66 06		IRELAND – Farnell Tel No: ++353 1 830 9277 Fax No: ++353 1 830 9016		RUSSIA – Farnell Tel No: ++44 870 1200 208 Fax No: ++44 870 1200 209	export EXPORT – Farnell Tel No: ++44 8701 200 208 Fax No: ++44 8701 200 209 For enquiries from all other markets	
	ESTONIA – Farnell Tel No: ++358 9 560 7780 Fax No: ++358 9 345 5411		ISRAEL – Farnell Tel No: ++180 937 0015 Fax No: ++180 937 0014		SINGAPORE – Farnell-Newark Tel No: ++65 6788 0200 Fax No: ++65 6788 0300	http://www.farnell.com http://www.newark.com http://www.cpc.co.uk	

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2008.

