



Series 801 Mighty Mouse Double Start ACME Thread Overmolded Harsh Environment Cordsets

801-026, -070, -034, and -071 Ordering Information

D

Series 801 Cordsets with #23 Contacts								
Sample Part Number								
801-026	-A	C	4	M	8-28	N	A	-36
Series	End A Connector	End B Connector	Wire Size	Shell Material/ Finish	Insert Arr.	Protective Cover	Shell Key Pos.	Length
801-026 Style 1 Polyurethane Cable Jacket, Polyamide Overmold #23 Contacts	-A Plug, with Male Pin Contacts	A Plug, with Male Pin Contacts	2 #22 AWG	M Aluminum / Electroless Nickel	See Cont. Arr. Page D-2	P Metal Protective Covers Included N No Covers Supplied	A Normal B Pos. B C Pos. C D Pos. D E Pos. E F Pos. F	Overall Length In Inches 12 Inch Min.
	-B Plug, with Female Socket Contacts	B Plug, with Female Socket Contacts	4 #24 AWG	NF Aluminum / Cadmium with OD Chromate	Consult Factory for Combo Arr.			
801-070 Style 2 Rubber Cable Jacket and Rubber Overmold #23 Contacts	-C Receptacle, with Male Pin Contacts	C Receptacle, with Male Pin Contacts		ZNU Aluminum / Zinc- Nickel with Black Chromate				
	-D Receptacle, with Female Socket Contacts	D Receptacle, with Female Socket Contacts		MT Aluminum / Nickel-PTFE				
		N No Connector (Single-Ended)		Z1 Stainless Steel / Passivated			See page D-2	

Series 801 Cordsets with #20HD Contacts								
Sample Part Number								
801-034	-A	C	0	M	8-28	N	A	-36
Series	End A Connector	End B Connector	Wire Size	Shell Material/ Finish	Insert Arr.	Protective Cover	Shell Key Pos.	Length
801-034 Style 1 Polyurethane Cable Jacket, Polyamide Overmold #20HD Contacts	-A Plug, with Male Pin Contacts	A Plug, with Male Pin Contacts	0 #20 AWG	M Aluminum / Electroless Nickel	See Cont. Arr. Page D-2	P Metal Protective Covers Included N No Covers Supplied	A Normal B Pos. B C Pos. C D Pos. D E Pos. E F Pos. F	Overall Length In Inches 12 Inch Min.
	-B Plug, with Female Socket Contacts	B Plug, with Female Socket Contacts	2 #22 AWG	NF Aluminum / Cadmium with OD Chromate	Consult Factory for Combo Arr.			
801-071 Style 2 Rubber Cable Jacket and Rubber Overmold #20HD Contacts	-C Receptacle, with Male Pin Contacts	C Receptacle, with Male Pin Contacts		ZNU Aluminum / Zinc- Nickel with Black Chromate				
	-D Receptacle, with Female Socket Contacts	D Receptacle, with Female Socket Contacts		MT Aluminum / Nickel-PTFE				
		N No Connector (Single-Ended)		Z1 Stainless Steel / Passivated			See page D-2	

Dimensions in Inches (millimeters) are subject to change without notice.