

# Cree® XLamp® CXA1310 LED



## PRODUCT DESCRIPTION

The XLamp CXA1310 is Cree's newest High Density (HD) LED array, featuring a 6-mm optical source and enabling lighting manufacturers to create a new generation of products that delivers the same intensity and light quality as 20-W ceramic metal halide (CMH) at up to 50 percent lower power. The new HD class of CXA arrays provide unrivaled lumen density that can reduce system cost for the next generation of LED spotlights.

The CXA LED Design Guide provides basic information on the requirements to use the CXA1310 LED successfully in luminaire designs.<sup>1</sup>

## FEATURES

- Available in 4-step and 2-step EasyWhite® bins at 2700 K, 3000 K, 3500 K, 4000 K, 5000 K, 5700 K and 6500 K CCT
- Available in ANSI white bins at 4000 K, 5000 K, 5700 K and 6500 K CCT
- Available in 70-, 80- and 93-minimum CRI options
- Forward voltage options: 18 V & 36 V
- 85 °C binning and characterization
- Maximum drive current: 1050 mA (18 V), 525mA (36 V)
- 115° viewing angle, uniform chromaticity profile
- Top-side solder connections
- Thermocouple attach point
- NEMA SSL-3 2011 standard flux bins

## TABLE OF CONTENTS

|                                                               |    |
|---------------------------------------------------------------|----|
| Characteristics .....                                         | 2  |
| Operating Limits.....                                         | 3  |
| Flux Characteristics, EasyWhite                               |    |
| Order Codes and Bins - 18 V .....                             | 4  |
| Flux Characteristics, ANSI White                              |    |
| Order Codes and Bins - 18 V .....                             | 5  |
| Flux Characteristics, EasyWhite                               |    |
| Order Codes and Bins - 36 V .....                             | 6  |
| Flux Characteristics, ANSI White                              |    |
| Order Codes and Bins - 36 V .....                             | 7  |
| Relative Spectral Power Distribution .                        | 8  |
| Electrical Characteristics.....                               | 9  |
| Relative Luminous Flux.....                                   | 10 |
| Typical Spatial Distribution.....                             | 12 |
| Performance Groups - Brightness....                           | 12 |
| Performance Groups - Chromaticity.                            | 13 |
| Cree EasyWhite Bins Plotted on the 1931 CIE Color Space ..... | 15 |
| Cree ANSI White Bins Plotted on the 1931 CIE Color Space..... | 15 |
| Bin and Order Code Formats .....                              | 16 |
| Mechanical Dimensions.....                                    | 16 |
| Thermal Design.....                                           | 17 |
| Notes.....                                                    | 18 |
| Packaging.....                                                | 19 |

<sup>1</sup> Cree XLamp CXA LED Design Guide, Design Guide DG02, [www.cree.com/xlamp\\_app\\_notes/cxa\\_design\\_guide](http://www.cree.com/xlamp_app_notes/cxa_design_guide)



## CHARACTERISTICS

| Characteristics                              | Unit    | Minimum | Typical | Maximum |
|----------------------------------------------|---------|---------|---------|---------|
| Viewing angle (FWHM)                         | degrees |         | 115     |         |
| ESD withstand voltage (HBM per Mil-Std-883D) | V       |         |         | 8000    |
| DC forward current (18 V)                    | mA      |         |         | 1050*   |
| DC forward current (36 V)                    | mA      |         |         | 525*    |
| Reverse current                              | mA      |         |         | 0.1     |
| Forward voltage (18 V, @ 700 mA, 85 °C)      | V       |         | 17.8    |         |
| Forward voltage (18 V, @ 700 mA, 25 °C)      | V       |         |         | 21      |
| Forward voltage (36 V, @ 350 mA, 85 °C)      | V       |         | 35.6    |         |
| Forward voltage (36 V, @ 350 mA, 25 °C)      | V       |         |         | 42      |

\* Refer to the Operating Limits section.

## OPERATING LIMITS

The maximum current rating of the CXA1310 is dependent on the case temperature ( $T_c$ ) when the LED has reached thermal equilibrium under steady-state operation. Please refer to the Mechanical Dimensions section on page 16 for the location of the  $T_c$  measurement point.



## FLUX CHARACTERISTICS, EASYWHITE ORDER CODES AND BINS - 18 V ( $I_F = 700 \text{ mA}$ , $T_J = 85 \text{ }^\circ\text{C}$ )

The following tables provide order codes for XLamp CXA1310 LEDs. For a complete description of the order code nomenclature, please reference Bin and Order Code Formats (page 16).

| CCT Range | CRI |     | Base Order Codes<br>Min. Luminous Flux<br>@ 700 mA |                   |                    | 2-Step Order Code   |                          | 4-Step Order Code   |                          |
|-----------|-----|-----|----------------------------------------------------|-------------------|--------------------|---------------------|--------------------------|---------------------|--------------------------|
|           | Min | Typ | Group                                              | Flux (lm) @ 85 °C | Flux (lm) @ 25 °C* | Chromaticity Region |                          | Chromaticity Region |                          |
| 6500 K    | 70  | 75  | K2                                                 | 1200              | 1344               |                     |                          | 65F                 | CXA1310-0000-000F00K265F |
|           |     |     | K4                                                 | 1290              | 1445               |                     |                          |                     | CXA1310-0000-000F00K465F |
|           | 80  | --- | J4                                                 | 1120              | 1255               |                     |                          | 65F                 | CXA1310-0000-000F0HJ465F |
|           |     |     | K2                                                 | 1200              | 1344               |                     |                          |                     | CXA1310-0000-000F0HK265F |
| 5700 K    | 70  | 75  | K2                                                 | 1200              | 1344               |                     |                          | 57F                 | CXA1310-0000-000F00K257F |
|           |     |     | K4                                                 | 1290              | 1445               |                     |                          |                     | CXA1310-0000-000F00K457F |
|           | 80  | --- | J4                                                 | 1120              | 1255               |                     |                          | 57F                 | CXA1310-0000-000F0HJ457F |
|           |     |     | K2                                                 | 1200              | 1344               |                     |                          |                     | CXA1310-0000-000F0HK257F |
| 5000 K    | 70  | 75  | K2                                                 | 1200              | 1344               | 50H                 | CXA1310-0000-000F00K250H | 50F                 | CXA1310-0000-000F00K250F |
|           |     |     | K4                                                 | 1290              | 1445               |                     | CXA1310-0000-000F00K450H |                     | CXA1310-0000-000F00K450F |
|           | 80  | --- | J4                                                 | 1120              | 1255               | 50H                 | CXA1310-0000-000F0HJ450H | 50F                 | CXA1310-0000-000F0HJ450F |
|           |     |     | K2                                                 | 1200              | 1344               |                     | CXA1310-0000-000F0HK250H |                     | CXA1310-0000-000F0HK250F |
| 4000 K    | 70  | 75  | K2                                                 | 1200              | 1344               | 40H                 | CXA1310-0000-000F00K240H | 40F                 | CXA1310-0000-000F00K240F |
|           |     |     | K4                                                 | 1290              | 1445               |                     | CXA1310-0000-000F00K440H |                     | CXA1310-0000-000F00K440F |
|           | 80  | --- | J4                                                 | 1120              | 1255               | 40H                 | CXA1310-0000-000F0HJ440H | 40F                 | CXA1310-0000-000F0HJ440F |
|           |     |     | K2                                                 | 1200              | 1344               |                     | CXA1310-0000-000F0HK240H |                     | CXA1310-0000-000F0HK240F |
| 3500 K    | 80  | --- | J2                                                 | 1040              | 1165               | 35H                 | CXA1310-0000-000F00J235H | 35F                 | CXA1310-0000-000F00J235F |
|           |     |     | J4                                                 | 1120              | 1255               |                     | CXA1310-0000-000F00J435H |                     | CXA1310-0000-000F00J435F |
|           | 93  | 95  | G4                                                 | 840               | 941                | 35H                 | CXA1310-0000-000F0YG435H | 35F                 | CXA1310-0000-000F0YG435F |
|           |     |     | H2                                                 | 900               | 1008               |                     | CXA1310-0000-000F0YH235H |                     | CXA1310-0000-000F0YH235F |
| 3000 K    | 80  | --- | J2                                                 | 1040              | 1165               | 30H                 | CXA1310-0000-000F00J230H | 30F                 | CXA1310-0000-000F00J230F |
|           |     |     | J4                                                 | 1120              | 1255               |                     | CXA1310-0000-000F00J430H |                     | CXA1310-0000-000F00J430F |
|           | 93  | 95  | G2                                                 | 780               | 881                | 30H                 | CXA1310-0000-000F0YG230H | 30H                 | CXA1310-0000-000F0YG230F |
|           |     |     | G4                                                 | 840               | 941                |                     | CXA1310-0000-000F0YG430H |                     | CXA1310-0000-000F0YG430F |
| 2700 K    | 80  | --- | H4                                                 | 970               | 1086               | 27H                 | CXA1310-0000-000F00H427H | 27F                 | CXA1310-0000-000F00H427F |
|           |     |     | J2                                                 | 1040              | 1165               |                     | CXA1310-0000-000F00J227H |                     | CXA1310-0000-000F00J227F |
|           | 93  | 95  | F4                                                 | 730               | 831                | 27H                 | CXA1310-0000-000F0YF427H | 27F                 | CXA1310-0000-000F0YF427F |
|           |     |     | G2                                                 | 780               | 881                |                     | CXA1310-0000-000F0YG227H |                     | CXA1310-0000-000F0YG227F |

### Notes

- Cree maintains a tolerance of  $\pm 7\%$  on flux and power measurements,  $\pm 0.005$  on chromaticity (CCx, CCy) measurements and a tolerance of  $\pm 2$  on CRI measurements.
- \* Flux values @ 25 °C are calculated and for reference only.

## FLUX CHARACTERISTICS, ANSI WHITE ORDER CODES AND BINS - 18 V ( $I_F = 700 \text{ mA}$ , $T_J = 85^\circ\text{C}$ )

The following tables provide order codes for XLamp CXA1310 LEDs. For a complete description of the order code nomenclature, please reference Bin and Order Code Formats (page 16).

| CCT Range | CRI |     | Base Order Codes<br>Min. Luminous Flux<br>@ 700 mA |                      |                       | Chromaticity Regions | Order Code               |
|-----------|-----|-----|----------------------------------------------------|----------------------|-----------------------|----------------------|--------------------------|
|           | Min | Typ | Group                                              | Flux (lm)<br>@ 85 °C | Flux (lm)<br>@ 25 °C* |                      |                          |
| 6500 K    | 70  | 75  | K2                                                 | 1200                 | 1344                  | 1A0, 1B0, 1C0, 1D0   | CXA1310-0000-000F00K20E1 |
|           |     |     | K4                                                 | 1290                 | 1445                  |                      | CXA1310-0000-000F00K40E1 |
|           | 80  | --- | J4                                                 | 1120                 | 1255                  | 1A0, 1B0, 1C0, 1D0   | CXA1310-0000-000F0HJ40E1 |
|           |     |     | K2                                                 | 1200                 | 1344                  |                      | CXA1310-0000-000F0HK20E1 |
| 5700 K    | 70  | 75  | K2                                                 | 1200                 | 1344                  | 2A0, 2B0, 2C0, 2D0   | CXA1310-0000-000F00K20E2 |
|           |     |     | K4                                                 | 1290                 | 1445                  |                      | CXA1310-0000-000F00K40E2 |
|           | 80  | --- | J4                                                 | 1120                 | 1255                  | 2A0, 2B0, 2C0, 2D0   | CXA1310-0000-000F0HJ40E2 |
|           |     |     | K2                                                 | 1200                 | 1344                  |                      | CXA1310-0000-000F0HK20E2 |
| 5000 K    | 70  | 75  | K2                                                 | 1200                 | 1344                  | 3A0, 3B0, 3C0, 3D0   | CXA1310-0000-000F00K20E3 |
|           |     |     | K4                                                 | 1290                 | 1445                  |                      | CXA1310-0000-000F00K40E3 |
|           | 80  | --- | J4                                                 | 1120                 | 1255                  | 3A0, 3B0, 3C0, 3D0   | CXA1310-0000-000F0HJ40E3 |
|           |     |     | K2                                                 | 1200                 | 1344                  |                      | CXA1310-0000-000F0HK20E3 |
| 4000 K    | 70  | 75  | K2                                                 | 1200                 | 1344                  | 5A0, 5B0, 5C0, 5D0   | CXA1310-0000-000F00K20E5 |
|           |     |     | K4                                                 | 1290                 | 1445                  |                      | CXA1310-0000-000F00K40E5 |
|           | 80  | --- | J4                                                 | 1120                 | 1255                  | 5A0, 5B0, 5C0, 5D0   | CXA1310-0000-000F0HJ40E5 |
|           |     |     | K2                                                 | 1200                 | 1344                  |                      | CXA1310-0000-000F0HK20E5 |

### Notes

- Cree maintains a tolerance of  $\pm 7\%$  on flux and power measurements,  $\pm 0.005$  on chromaticity (CCx, CCy) measurements and a tolerance of  $\pm 2$  on CRI measurements.
- \* Flux values @ 25 °C are calculated and for reference only.

## FLUX CHARACTERISTICS, EASYWHITE ORDER CODES AND BINS - 36 V ( $I_F = 350 \text{ mA}$ , $T_J = 85 \text{ }^\circ\text{C}$ )

The following tables provide order codes for XLamp CXA1310 LEDs. For a complete description of the order code nomenclature, please reference Bin and Order Code Formats (page 16).

| CCT Range | CRI |     | Base Order Codes<br>Min. Luminous Flux<br>@ 350 mA |                   |                    | 2-Step Order Code   |                          | 4-Step Order Code   |                          |
|-----------|-----|-----|----------------------------------------------------|-------------------|--------------------|---------------------|--------------------------|---------------------|--------------------------|
|           | Min | Typ | Group                                              | Flux (lm) @ 85 °C | Flux (lm) @ 25 °C* | Chromaticity Region |                          | Chromaticity Region |                          |
| 6500 K    | 70  | 75  | K2                                                 | 1200              | 1344               |                     |                          | 65F                 | CXA1310-0000-000N00K265F |
|           |     |     | K4                                                 | 1290              | 1445               |                     |                          |                     | CXA1310-0000-000N00K465F |
|           | 80  | --- | J4                                                 | 1120              | 1255               |                     |                          | 65F                 | CXA1310-0000-000N0HJ465F |
|           |     |     | K2                                                 | 1200              | 1344               |                     |                          |                     | CXA1310-0000-000N0HK265F |
| 5700 K    | 70  | 75  | K2                                                 | 1200              | 1344               |                     |                          | 57F                 | CXA1310-0000-000N00K257F |
|           |     |     | K4                                                 | 1290              | 1445               |                     |                          |                     | CXA1310-0000-000N00K457F |
|           | 80  | --- | J4                                                 | 1120              | 1255               |                     |                          | 57F                 | CXA1310-0000-000N0HJ457F |
|           |     |     | K2                                                 | 1200              | 1344               |                     |                          |                     | CXA1310-0000-000N0HK257F |
| 5000 K    | 70  | 75  | K2                                                 | 1200              | 1344               | 50H                 | CXA1310-0000-000N00K250H | 50F                 | CXA1310-0000-000N00K250F |
|           |     |     | K4                                                 | 1290              | 1445               |                     | CXA1310-0000-000N00K450H |                     | CXA1310-0000-000N00K450F |
|           | 80  | --- | J4                                                 | 1120              | 1255               | 50H                 | CXA1310-0000-000N0HJ450H | 50F                 | CXA1310-0000-000N0HJ450F |
|           |     |     | K2                                                 | 1200              | 1344               |                     | CXA1310-0000-000N0HK250H |                     | CXA1310-0000-000N0HK250F |
| 4000 K    | 70  | 75  | K2                                                 | 1200              | 1344               | 40H                 | CXA1310-0000-000N00K240H | 40F                 | CXA1310-0000-000N00K240F |
|           |     |     | K4                                                 | 1290              | 1445               |                     | CXA1310-0000-000N00K440H |                     | CXA1310-0000-000N00K440F |
|           | 80  | --- | J4                                                 | 1120              | 1255               | 40H                 | CXA1310-0000-000N0HJ440H | 40F                 | CXA1310-0000-000N0HJ440F |
|           |     |     | K2                                                 | 1200              | 1344               |                     | CXA1310-0000-000N0HK240H |                     | CXA1310-0000-000N0HK240F |
| 3500 K    | 80  | --- | J2                                                 | 1040              | 1165               | 35H                 | CXA1310-0000-000N00J235H | 35F                 | CXA1310-0000-000N00J235F |
|           |     |     | J4                                                 | 1120              | 1255               |                     | CXA1310-0000-000N00J435H |                     | CXA1310-0000-000N00J435F |
|           | 93  | 95  | G4                                                 | 840               | 941                | 35H                 | CXA1310-0000-000N0YG435H | 35F                 | CXA1310-0000-000N0YG435F |
|           |     |     | H2                                                 | 900               | 1008               |                     | CXA1310-0000-000N0YH235H |                     | CXA1310-0000-000N0YH235F |
| 3000 K    | 80  | --- | J2                                                 | 1040              | 1165               | 30H                 | CXA1310-0000-000N00J230H | 30F                 | CXA1310-0000-000N00J230F |
|           |     |     | J4                                                 | 1120              | 1255               |                     | CXA1310-0000-000N00J430H |                     | CXA1310-0000-000N00J430F |
|           | 93  | 95  | G2                                                 | 780               | 881                | 30H                 | CXA1310-0000-000N0YG230H | 30H                 | CXA1310-0000-000N0YG230F |
|           |     |     | G4                                                 | 840               | 941                |                     | CXA1310-0000-000N0YG430H |                     | CXA1310-0000-000N0YG430F |
| 2700 K    | 80  | --- | H4                                                 | 970               | 1086               | 27H                 | CXA1310-0000-000N00H427H | 27F                 | CXA1310-0000-000N00H427F |
|           |     |     | J2                                                 | 1040              | 1165               |                     | CXA1310-0000-000N00J227H |                     | CXA1310-0000-000N00J227F |
|           | 93  | 95  | F4                                                 | 730               | 831                | 27H                 | CXA1310-0000-000N0YF427H | 27F                 | CXA1310-0000-000N0YF427F |
|           |     |     | G2                                                 | 780               | 881                |                     | CXA1310-0000-000N0YG227H |                     | CXA1310-0000-000N0YG227F |

### Notes

- Cree maintains a tolerance of  $\pm 7\%$  on flux and power measurements,  $\pm 0.005$  on chromaticity (CCx, CCy) measurements and a tolerance of  $\pm 2$  on CRI measurements.
- \* Flux values @ 25 °C are calculated and for reference only.

## FLUX CHARACTERISTICS, ANSI WHITE ORDER CODES AND BINS - 36 V ( $I_F = 350$ mA, $T_J = 85$ °C)

The following tables provide order codes for XLamp CXA1310 LEDs. For a complete description of the order code nomenclature, please reference Bin and Order Code Formats (page 16).


| CCT Range | CRI |     | Base Order Codes<br>Min. Luminous Flux<br>@ 350 mA |                      |                       | Chromaticity Regions | Order Code               |
|-----------|-----|-----|----------------------------------------------------|----------------------|-----------------------|----------------------|--------------------------|
|           | Min | Typ | Group                                              | Flux (lm)<br>@ 85 °C | Flux (lm)<br>@ 25 °C* |                      |                          |
| 6500 K    | 70  | 75  | K2                                                 | 1200                 | 1344                  | 1A0, 1B0, 1C0, 1D0   | CXA1310-0000-000N00K20E1 |
|           |     |     | K4                                                 | 1290                 | 1445                  |                      | CXA1310-0000-000N00K40E1 |
|           | 80  | --- | J4                                                 | 1120                 | 1255                  | 1A0, 1B0, 1C0, 1D0   | CXA1310-0000-000N0HJ40E1 |
|           |     |     | K2                                                 | 1200                 | 1344                  |                      | CXA1310-0000-000N0HK20E1 |
| 5700 K    | 70  | 75  | K2                                                 | 1200                 | 1344                  | 2A0, 2B0, 2C0, 2D0   | CXA1310-0000-000N00K20E2 |
|           |     |     | K4                                                 | 1290                 | 1445                  |                      | CXA1310-0000-000N00K40E2 |
|           | 80  | --- | J4                                                 | 1120                 | 1255                  | 2A0, 2B0, 2C0, 2D0   | CXA1310-0000-000N0HJ40E2 |
|           |     |     | K2                                                 | 1200                 | 1344                  |                      | CXA1310-0000-000N0HK20E2 |
| 5000 K    | 70  | 75  | K2                                                 | 1200                 | 1344                  | 3A0, 3B0, 3C0, 3D0   | CXA1310-0000-000N00K20E3 |
|           |     |     | K4                                                 | 1290                 | 1445                  |                      | CXA1310-0000-000N00K40E3 |
|           | 80  | --- | J4                                                 | 1120                 | 1255                  | 3A0, 3B0, 3C0, 3D0   | CXA1310-0000-000N0HJ40E3 |
|           |     |     | K2                                                 | 1200                 | 1344                  |                      | CXA1310-0000-000N0HK20E3 |
| 4000 K    | 70  | 75  | K2                                                 | 1200                 | 1344                  | 5A0, 5B0, 5C0, 5D0   | CXA1310-0000-000N00K20E5 |
|           |     |     | K4                                                 | 1290                 | 1445                  |                      | CXA1310-0000-000N00K40E5 |
|           | 80  | --- | J4                                                 | 1120                 | 1255                  | 5A0, 5B0, 5C0, 5D0   | CXA1310-0000-000N0HJ40E5 |
|           |     |     | K2                                                 | 1200                 | 1344                  |                      | CXA1310-0000-000N0HK20E5 |

### Notes

- Cree maintains a tolerance of  $\pm 7\%$  on flux and power measurements,  $\pm 0.005$  on chromaticity (CCx, CCy) measurements and a tolerance of  $\pm 2$  on CRI measurements.
- \* Flux values @ 25 °C are calculated and for reference only.

### RELATIVE SPECTRAL POWER DISTRIBUTION (18 V, $I_F = 700$ mA; 36 V, $I_F = 350$ mA, $T_J = 85$ °C)



The following graph is the result of a series of pulsed measurements at 350 mA for the 18-V CXA1310 LED and 700 mA for the 36-V CXA1310 LED and  $T_J = 85$  °C.





## ELECTRICAL CHARACTERISTICS

The following graph is the result of a series of steady-state measurements.




## RELATIVE LUMINOUS FLUX

The relative luminous flux values provided below are the ratio of:

- Measurements of CXA1310 at steady-state operation at the given conditions, divided by
- Flux measured during binning, which is a pulsed measurement at 700 mA at  $T_j = 85^\circ\text{C}$  for the 18-V CXA1310 LED.

For example, at steady-state operation of  $T_c = 55^\circ\text{C}$ ,  $I_f = 500\text{ mA}$ , the relative luminous flux ratio is 80% in the chart below. A CXA1310 LED that measures 1200 lm during binning will deliver 960 lm ( $1200 \times 0.8$ ) at steady-state operation of  $T_c = 55^\circ\text{C}$ ,  $I_f = 500\text{ mA}$ .




## RELATIVE LUMINOUS FLUX - CONTINUED


The relative luminous flux values provided below are the ratio of:

- Measurements of CXA1310 at steady-state operation at the given conditions, divided by
- Flux measured during binning, which is a pulsed measurement at 350 mA at  $T_j = 85\text{ }^{\circ}\text{C}$  for the 36-V CXA1310 LED.

For example, at steady-state operation of  $T_c = 55\text{ }^{\circ}\text{C}$ ,  $I_f = 250\text{ mA}$ , the relative luminous flux ratio is 80% in the chart below. A CXA1310 LED that measures 1200 lm during binning will deliver 960 lm ( $1200 \times 0.8$ ) at steady-state operation of  $T_c = 55\text{ }^{\circ}\text{C}$ ,  $I_f = 250\text{ mA}$ .



## TYPICAL SPATIAL DISTRIBUTION



## PERFORMANCE GROUPS - BRIGHTNESS (18 V, $I_F = 700$ mA; 36 V, $I_F = 350$ mA, $T_J = 85$ °C)

XLamp CXA1310 LEDs are tested for luminous flux and placed into one of the following bins.

| Group Code | Min. Luminous Flux | Max. Luminous Flux |
|------------|--------------------|--------------------|
| F4         | 730                | 780                |
| G2         | 780                | 840                |
| G4         | 840                | 900                |
| H2         | 900                | 970                |
| H4         | 970                | 1040               |
| J2         | 1040               | 1120               |
| J4         | 1120               | 1200               |
| K2         | 1200               | 1290               |
| K4         | 1290               | 1380               |

## PERFORMANCE GROUPS - CHROMATICITY ( $T_j = 85\text{ }^{\circ}\text{C}$ )

XLamp CXA1310 LEDs are tested for chromaticity and placed into one of the regions defined by the following bounding coordinates.

| EasyWhite Color Temperatures – 4-Step |        |        |        |
|---------------------------------------|--------|--------|--------|
| Code                                  | CCT    | x      | y      |
| 65F                                   | 6500 K | 0.3253 | 0.3325 |
|                                       |        | 0.3249 | 0.3439 |
|                                       |        | 0.3331 | 0.3514 |
|                                       |        | 0.3330 | 0.3393 |
| 57F                                   | 5700 K | 0.3097 | 0.3196 |
|                                       |        | 0.3079 | 0.3297 |
|                                       |        | 0.3164 | 0.3382 |
|                                       |        | 0.3176 | 0.3275 |
| 50F                                   | 5000 K | 0.3407 | 0.3459 |
|                                       |        | 0.3415 | 0.3586 |
|                                       |        | 0.3499 | 0.3654 |
|                                       |        | 0.3484 | 0.3521 |
| 40F                                   | 4000 K | 0.3744 | 0.3685 |
|                                       |        | 0.3782 | 0.3837 |
|                                       |        | 0.3912 | 0.3917 |
|                                       |        | 0.3863 | 0.3758 |
| 35F                                   | 3500 K | 0.3981 | 0.3800 |
|                                       |        | 0.4040 | 0.3966 |
|                                       |        | 0.4186 | 0.4037 |
|                                       |        | 0.4116 | 0.3865 |
| 30F                                   | 3000 K | 0.4242 | 0.3919 |
|                                       |        | 0.4322 | 0.4096 |
|                                       |        | 0.4449 | 0.4141 |
|                                       |        | 0.4359 | 0.3960 |
| 27F                                   | 2700 K | 0.4475 | 0.3994 |
|                                       |        | 0.4573 | 0.4178 |
|                                       |        | 0.4695 | 0.4207 |
|                                       |        | 0.4589 | 0.4021 |

| EasyWhite Color Temperatures – 2-Step |       |        |        |
|---------------------------------------|-------|--------|--------|
| Code                                  | CCT   | x      | y      |
| 50H                                   | 5000K | 0.3429 | 0.3507 |
|                                       |       | 0.3434 | 0.3571 |
|                                       |       | 0.3475 | 0.3604 |
|                                       |       | 0.3469 | 0.3539 |
| 40H                                   | 4000K | 0.3784 | 0.3741 |
|                                       |       | 0.3804 | 0.3818 |
|                                       |       | 0.3867 | 0.3857 |
|                                       |       | 0.3844 | 0.3778 |
| 35H                                   | 3500K | 0.4030 | 0.3857 |
|                                       |       | 0.4061 | 0.3941 |
|                                       |       | 0.4132 | 0.3976 |
|                                       |       | 0.4099 | 0.3890 |
| 30H                                   | 3000K | 0.4291 | 0.3973 |
|                                       |       | 0.4333 | 0.4062 |
|                                       |       | 0.4395 | 0.4084 |
|                                       |       | 0.4351 | 0.3994 |
| 27H                                   | 2700K | 0.4528 | 0.4046 |
|                                       |       | 0.4578 | 0.4138 |
|                                       |       | 0.4638 | 0.4152 |
|                                       |       | 0.4586 | 0.4060 |

**PERFORMANCE GROUPS - CHROMATICITY ( $T_j = 85\text{ }^{\circ}\text{C}$ ) - CONTINUED**


| ANSI White Bins |        |          |        |        |
|-----------------|--------|----------|--------|--------|
| Code            | CCT    | Bin Code | x      | y      |
| 0E1             | 6500 K | 1A0      | 0.3048 | 0.3207 |
|                 |        |          | 0.3130 | 0.3290 |
|                 |        |          | 0.3144 | 0.3186 |
|                 |        |          | 0.3068 | 0.3113 |
|                 |        | 1B0      | 0.3028 | 0.3304 |
|                 |        |          | 0.3115 | 0.3391 |
|                 |        |          | 0.3130 | 0.3290 |
|                 |        |          | 0.3048 | 0.3207 |
|                 |        | 1C0      | 0.3115 | 0.3391 |
|                 |        |          | 0.3205 | 0.3481 |
|                 |        |          | 0.3213 | 0.3373 |
|                 |        |          | 0.3130 | 0.3290 |
|                 |        | 1D0      | 0.3130 | 0.3290 |
|                 |        |          | 0.3213 | 0.3373 |
|                 |        |          | 0.3221 | 0.3261 |
|                 |        |          | 0.3144 | 0.3186 |

| ANSI White Bins |        |          |        |        |
|-----------------|--------|----------|--------|--------|
| Code            | CCT    | Bin Code | x      | y      |
| 0E2             | 5700 K | 2A0      | 0.3215 | 0.3350 |
|                 |        |          | 0.3290 | 0.3417 |
|                 |        |          | 0.3290 | 0.3300 |
|                 |        |          | 0.3222 | 0.3243 |
|                 |        | 2B0      | 0.3207 | 0.3462 |
|                 |        |          | 0.3290 | 0.3538 |
|                 |        |          | 0.3290 | 0.3417 |
|                 |        |          | 0.3215 | 0.3350 |
|                 |        | 2C0      | 0.3290 | 0.3538 |
|                 |        |          | 0.3376 | 0.3616 |
|                 |        |          | 0.3371 | 0.3490 |
|                 |        |          | 0.3290 | 0.3417 |
|                 |        | 2D0      | 0.3290 | 0.3417 |
|                 |        |          | 0.3371 | 0.3490 |
|                 |        |          | 0.3366 | 0.3369 |
|                 |        |          | 0.3290 | 0.3300 |


| ANSI White Bins |       |          |       |       |
|-----------------|-------|----------|-------|-------|
| Code            | CCT   | Bin Code | x     | y     |
| 0E3             | 5000K | 3A0      | .3371 | .3490 |
|                 |       |          | .3451 | .3554 |
|                 |       |          | .3440 | .3427 |
|                 |       |          | .3366 | .3369 |
|                 |       | 3B0      | .3376 | .3616 |
|                 |       |          | .3463 | .3687 |
|                 |       |          | .3451 | .3554 |
|                 |       |          | .3371 | .3490 |
|                 |       | 3C0      | .3463 | .3687 |
|                 |       |          | .3551 | .3760 |
|                 |       |          | .3533 | .3620 |
|                 |       |          | .3451 | .3554 |
|                 |       | 3D0      | .3451 | .3554 |
|                 |       |          | .3533 | .3620 |
|                 |       |          | .3515 | .3487 |
|                 |       |          | .3440 | .3427 |

| ANSI White Bins |       |          |       |       |
|-----------------|-------|----------|-------|-------|
| Code            | CCT   | Bin Code | x     | y     |
| 0E5             | 4000K | 5A0      | .3670 | .3578 |
|                 |       |          | .3702 | .3722 |
|                 |       |          | .3825 | .3798 |
|                 |       |          | .3783 | .3646 |
|                 |       | 5B0      | .3702 | .3722 |
|                 |       |          | .3736 | .3874 |
|                 |       |          | .3869 | .3958 |
|                 |       |          | .3825 | .3798 |
|                 |       | 5C0      | .3825 | .3798 |
|                 |       |          | .3869 | .3958 |
|                 |       |          | .4006 | .4044 |
|                 |       |          | .3950 | .3875 |
|                 |       | 5D0      | .3783 | .3646 |
|                 |       |          | .3825 | .3798 |
|                 |       |          | .3950 | .3875 |
|                 |       |          | .3898 | .3716 |

## CREE EASYWHITE BINS PLOTTED ON THE 1931 CIE COLOR SPACE ( $T_j = 85^\circ\text{C}$ )




## CREE ANSI WHITE BINS PLOTTED ON THE 1931 CIE COLOR SPACE ( $T_j = 85^\circ\text{C}$ )



## BIN AND ORDER CODE FORMATS

Bin codes and order codes are configured as follows:



## MECHANICAL DIMENSIONS

Dimensions are in mm.


Tolerances unless otherwise specified:

.x ± .10

.xx ± .03

.xxx ± .010

x° ± 1°







## THERMAL DESIGN

The CXA family of LED arrays can include over a hundred different LED die inside one package, and thus over a hundred different junction temperatures ( $T_j$ ). Cree has intentionally removed junction-temperature-based operating limits and replaced the commonplace maximum  $T_j$  calculations with maximum ratings based on forward current ( $I_f$ ) and case temperature ( $T_c$ ). No additional calculations are required to ensure the CXA LED is being operated within its designed limits. Please refer to page 2 for the Operating Limit specification.


Cree has measured the temperature at the bottom of the package, commonly referred to as the solder point ( $T_{sp}$ ), and found this value to be equivalent to the temperature at the  $T_c$  location at the top of the package once the LED has reached thermal equilibrium. There is no need to calculate for  $T_j$  inside the package, as the thermal management design process, specifically from  $T_{sp}$  to ambient ( $T_a$ ), remains identical to any other LED component. For more information on thermal management of Cree XLamp LEDs, please refer to the XLamp Thermal Management application note at [www.cree.com/xlamp\\_app\\_notes/thermal\\_management](http://www.cree.com/xlamp_app_notes/thermal_management). For CXA soldering recommendations and more information on thermal interface materials (TIM) and connection methods, please refer to the Cree XLamp CXA Family LEDs soldering and handling document at [www.cree.com/xlamp\\_app\\_notes/CXA\\_SH](http://www.cree.com/xlamp_app_notes/CXA_SH).

To keep the CXA1310 LED at or below the maximum rated  $T_c$ , the case to ambient thermal resistance ( $R_{c-a}$ ) must be at or below the maximum  $R_{c-a}$  value shown on the following graphs, depending on the operating environment. The y-axis in the graph is a base 10 logarithmic scale.

As the figure at right shows, the  $R_{c-a}$  value is the sum of the thermal resistance of the TIM ( $R_{tim}$ ) plus the thermal resistance of the heat sink ( $R_{hs}$ ).



## THERMAL DESIGN - CONTINUED



## NOTES

### Lumen Maintenance Projections

Cree now uses standardized IES LM-80-08 and TM-21-11 methods for collecting long-term data and extrapolating LED lumen maintenance. For information on the specific LM-80 data sets available for this LED, refer to the public LM-80 results document at [www.cree.com/xlamp\\_app\\_notes/LM80\\_results](http://www.cree.com/xlamp_app_notes/LM80_results).

Please read the XLamp Long-Term Lumen Maintenance application note at [www.cree.com/xlamp\\_app\\_notes/lumen\\_maintenance](http://www.cree.com/xlamp_app_notes/lumen_maintenance) for more details on Cree's lumen maintenance testing and forecasting. Please read the XLamp Thermal Management application note at [www.cree.com/xlamp\\_app\\_notes/thermal\\_management](http://www.cree.com/xlamp_app_notes/thermal_management) for details on how thermal design, ambient temperature, and drive current affect the LED junction temperature.

### Vision Advisory Claim

Users should be cautioned not to stare at the light of this LED product. The bright light can damage the eye.

### PACKAGING

Cree CXA1310 LEDs are packaged in trays of 20. Five trays are sealed in an anti-static bag and placed inside a carton, for a total of 100 LEDs per carton. Each carton contains 100 LEDs from the same performance bin.

Dimensions are in inches.



Tolerances:

.x  $\pm$  .1


.xx  $\pm$  .03

.xxx  $\pm$  .010

x°  $\pm$  1°



PATENT LABEL IS LOCATED ON UNDERSIDE OF CARTON



WITH CREE BIN CODE, QTY, LOT #

BAG

