

Data Sheet

PM202xxVBDN

Page 1/4


P/N

PM202xxVBDN

xx=number of poles

2017/05/05

Illustration



see enlarged drawing at the end of the document

Product specification

- pin header, SMT solderable
- centerline 2.54 mm, direction of connection vertical 0°
- color black
- Tape & Reel packaging
- dual rows

© 2017 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!



Data Sheet

PM202xxVBDN

Technical Data

General Data

min. number of poles	2
max. number of poles	40

Approvals

Rated current	3 A
---------------	-----

Material

insulating material	PE-HT
contact material	CuZn
Glow-Wire Flammability GWFI	-
Glow-Wire Flammability GWIT	-
contact surface	Ni + Au
contact pin material	CuZn
contact pin surface	Ni + Au Flash

Climatic properties

upper limit temperature	105 °C
lower limit temperature	-40 °C

General

solderability	Acc. to IPC/JEDEC J-STD-020D-MSL 1
Tolerance	ISO 2768 -mH






Data Sheet

PM202xxVBDN

Illustration

Drawing



$$L = (\text{pole size} - 1) \times \text{centerline} + 2.54 [0.1]$$

Data Sheet

PM202xxVBDN

Page 4/4

P/N

PM202xxVBDN

xx=number of poles

2017/05/05

PCB Layout

