TAIWAN SEMICONDUCTOR

The Smartest Choice

SRA1020 - SRA10150

10.0AMPS. Schottky Barrier Rectifiers

TO-220AC

Pb-Free

RoHS COMPLIANT

Features

- ✧ Low power loss, high efficiency
- ✧ High current capability, low VF
- ✧ High reliabbility
- ✧ High surge current capability
- ✧ Epitaxial construction
- ✧ Guard-ring for transient protection
- ✧ For use in low voltage, high frequency inverter, free wheeling, and polarity protection application
- ✧ Green compound with suffix "G" on packing code & prefix "G" on datecode

Mechanical Data

- ✧ Case: TO-220AC molded plastic
- ✧ Epoxy: UL 94V-0 rate flame retardant
- ✧ Terminals: Pure tin plated, lead free, solderable per MIL-STD-202, Method 208 guaranteed
- ✧ Polarity: As marked
- ✧ High temperature soldering guaranteed: 260℃/10 seconds/.25", (6.35mm) from case
- ✧ Weight: 1.87 gram

Ordering Information(example)

Part No.	Package	Packing	Packing code	Packing code (Green)
SRA1020	TO-220AC	50 / TUBE	C0	C0G

Maximum Ratings and Electrical Characteristics

Rating at 25 ℃ ambient temperature unless otherwise specified.

Parameter	Symbol	SRA 1020	SRA 1030	SRA 1040	SRA 1050	SRA 1060	SRA 1090	SRA 10100	SRA 10150	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	30	40	50	60	90	100	150	V
Maximum RMS Voltage	V_{RMS}	14	21	28	35	42	63	70	105	V
Maximum DC Blocking Voltage	V_{DC}	20	30	40	50	60	90	100	150	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	10								A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	170								A
Maximum Instantaneous Forward Voltage (Note 1) @ 10A	V_F	0.55			0.70		0.85		0.95	V
Maximum Reverse Current @ Rated VR T_A=25 ℃	I_R	0.5					0.1			mA
T_A=100 ℃		15			10		-			
T_A=125℃		-					5			
Typical Junction Capacitance (Note 2)	Cj	400								pF
Typical Thermal Resistance	$R_{\theta jC}$	2								^{O}C/W
Operating Temperature Range	T_J	- 65 to + 125			- 65 to + 150					^{O}C
Storage Temperature Range	T_{STG}	- 65 to + 150								^{O}C

Note 1 : Pulse Test : 300 usec Pulse Width, 1% Duty Cycle

Note 2 : Measure at 1MHz and Applied Reverse Voltage of 4.0V D.C.

TAIWAN SEMICONDUCTOR
The Smartest Choice

RATINGS AND CHARACTERISTIC CURVES (SRA1020 THRU SRA10150)

FIG.1 FORWARD CURRENT DERATING CURVE



FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT



FIG. 3 TYPICAL FORWARD CHARACTERISTICS



FIG. 4 TYPICAL REVERSE CHARACTERISTICS



FIG. 5 TYPICAL JUNCTION CAPACITANCE



FIG. 6 TYPICAL TRANSIENT THERMAL IMPEDANCE



Version:H12

Ordering information

Part No.	Package	BULK Packing	Packing code	Packing code (Green)
SRA10xx	TO-220AC	50 / TUBE	C0	C0G

Note: "xx" is Device Code from "20" thru "150".

Dimensions



DIM.	Unit(mm)		Unit(inch)	
	Min	Max	Min	Max
A	-	10.50	-	0.413
B	2.62	3.44	0.103	0.135
C	2.80	4.20	0.110	0.165
D	0.68	0.94	0.027	0.037
E	3.54	4.00	0.139	0.157
F	14.60	16.00	0.575	0.630
G	-	1.60	-	0.063
H	13.19	14.79	0.519	0.582
I	4.95	5.20	0.195	0.205
J	4.42	4.76	0.174	0.187
K	1.14	1.40	0.045	0.055
L	5.84	6.86	0.230	0.270
M	2.20	2.80	0.087	0.110
N	0.35	0.64	0.014	0.025



Marking Diagram

P/N = Specific Device Code
G = Green Compound
YWW = Date Code