


Sales Region	Worldwide (except Japan)
Series	DRB
Model	DRB-3PH
Status	 Production
Feature	Peak power capability
Options	
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to here.
Brand	TDK-Lambda



Electrical Characteristics

Input	3-phase
Input Voltage Range[AC]	350 to 575Vac
Input Voltage Range[DC]	
Efficiency	89.4% Typ.
Rated Output Voltage[DC]	12Vdc
Output Voltage Range[DC]	11.4 to 15Vdc
Maximum Output Current	10A
Maximum Average Current	
Maximum Peak Current	
Maximum Output Power	120W
Maximum Average Power	
Maximum Peak Power	144W

Package Type & Size

Package / Mounting	DIN rail
Industry Standard Size	
Width(W)	55mm Nom. (2.17in Nom.)
Height(H)	129mm Nom. (5.08in Nom.)
Depth(D)	135.7mm Nom. (5.34in Nom.)
Weight	660g Typ. (1.5lbs Typ.)

Other

Operating Temp. Range	-25 to 70°C
Cooling	Convection

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

	IEC61010-1
	EN61010-1
	UL61010-1
Safety Standard(Certified)	IEC62368-1
	EN62368-1
	UL62368-1
	CE Mark

Safety Standard(Conformed)

Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.
---------	---

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.