

ADAM-4021

ADAM-4022T

ADAM-4024

1-ch Analog Output Module

2-ch Serial Based Dual Loop PID Controller with Modbus

4-ch Analog Output Module with Modbus



ADAM-4021



ADAM-4022T



ADAM-4024



Specifications

General

- Connectors 2 x plug-in terminal blocks (#14 ~ 22 AWG)
- Power Consumption 1.4 W @ 24 V_{DC}
- Watchdog Timer System (1.6 second)
- Supported Protocols ASCII command

Analog Output

- Channels 1
- Output Impedance 0.5 Ω
- Output Range 0 ~ 20 mA, 4 ~ 20 mA, 0 ~ 10 V
- Output Type mA, V
- Accuracy ±0.1% of FSR for current output
±0.2% of FSR for voltage output
- Current Load Resistor 0 to 500 Ω (source)
- Resolution 12-bit
- Isolation Voltage 3,000 V_{DC}
- Programmable Output Slope 0.125 ~ 128 mA/sec.
0.0625 ~ 64.0 V/sec.
- Readback Accuracy ±1% of FSR
- Span Temperature Coefficient ±25 ppm/°C
- Zero Drift Voltage output: ±30 μV/°C
current output: ±0.2 μA/°C

Common Specifications

General

- Power Input Unregulated 10 ~ 30 V_{DC}

Environment

- Humidity 5 ~ 95% RH
- Operating Temperature -10 ~ 70° C
(14 ~ 158° F)
- Storage Temperature -25 ~ 85° C
(-13 ~ 185° F)

Specifications

General

- Connectors 2 x plug-in terminal blocks (#14 ~ 28 AWG)
- Power Consumption 4 W @ 24 V_{DC}
- Watchdog Timer System (1.6 second)
- Supported Protocols ASCII command and Modbus/RTU

Analog Input

- Channels 4
- Input Type mA, V, Thermistor, RTD
- Input Range 0 ~ 20 mA, 4 ~ 20 mA, 0 ~ 10 V
- Thermistor Type and Temperature Ranges Thermistor 3 K: 0 ~ 100° C
Thermistor 10 K: 0 ~ 100° C
- RTD Type and Temperature Ranges Pt 100 RTD Pt 0 ~ 100° C Pt -100 ~ 100° C
Pt 0 ~ 600° C Pt 0 ~ 200° C
IEC RTD 100 ohms (α = 0.00385)
JIS RTD 100 ohms (α = 0.00392)
Pt 1000 RTD Pt -40 ~ 160° C
- Resolution 16-bit
- Sampling Rate 10 sample/second
- Isolation Voltage 3,000 V_{DC}

Analog Output

- Channels 2
- Output Range 0 ~ 20 mA, 4 ~ 20 mA, 0 ~ 10 V
- Output Type mA, V
- Resolution 12-bit
- Isolation Voltage 3,000 V_{DC}

Digital Input

- Channels 2
- Dry Contact Logic level 0-close to GND
Logic level 1-open

Digital Output

- Channels 2
- Open Collector to 30 V, 30 mA max. load
- Power Dissipation 300 mW

Specifications

General

- Connectors 2 x plug-in terminal blocks (#14 ~ 28 AWG)
- Power Consumption 3 W @ 24 V_{DC}
- Watchdog Timer System (1.6 second) & Communication
- Supported Protocols ASCII command and Modbus/RTU

Analog Output

- Channels 4
- Output Impedance 0.5 Ω
- Output Range 0 ~ 20 mA, 4 ~ 20mA, ±10 V
- Output Type mA, V
- Accuracy ±0.1 % of FSR for current output
±0.1 % of FSR for voltage output
- Current Load Resistor 0 to 500 Ω (source)
- Resolution 12-bit
- Isolation Voltage 3,000 V_{DC}
- Programmable Output Slope 0.125 ~ 128 mA/sec.
0.0625 ~ 64.0 V/sec.
- Span Temperature ±25 ppm/°C
Coefficient
- Zero Drift Voltage output: ±30 μV/°C
Current output: ±0.2 μA/°C

Digital Input

- Channels 4
- Input Level Logic level 0: +1V max
Logic level 1: 10 ~ 30 V_{DC}
- Isolation Voltage 3,000 V_{DC}

Ordering Information

- ADAM-4021 1-ch Analog Output Module
- ADAM-4022T 2-ch Serial Based Dual Loop PID Controller w/ Modbus
- ADAM-4024 4-ch Analog Output Module with Modbus