




Glass fiber optic FE-BNSRA5S-3

- Cylindrical sensing head
- Side view / periscope optics
- Durable stainless steel sheathing

Glass fiber optic - diffuse

Dimensions



Technical Data

General specifications

Sensor range		MHP-FR: 32 mm MHP-F: 62 mm RL(K)61-LL: 155 mm MPG6HD: 170 mm
Fiber optic length	l	3 ft (.914 m)
End piece		Optical axis: Side view / periscope Type: Cylindrical / smooth barrel
Bending radius		min. 25 mm
Fiber bundle diameter		2.3 mm

Ambient conditions

Ambient temperature		-40 ... 232 °C (-40 ... 449.6 °F)
---------------------	--	-----------------------------------

Mechanical specifications

Material		
Optical face		glass
Sheathing		Stainless steel 1.4305 / AISI 303
Core		glass
End piece		Stainless steel 1.4305 / AISI 303
Adapter		Stainless steel, 4.7 mm diameter

Release date: 2020-11-02 Date of issue: 2020-11-02 Filename: 904819_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 PEPPERL+FUCHS

Technical Data

Fiber optic amplifiers

Device series	MP, MHP, Series 61
---------------	--------------------

Installation

Note: If after installing the device the yellow signal indicator lights up or flashes, the sensor detects a nonexisting object. Reduce the sensitivity of the sensor.

Application

Attention:

Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.

