

**Pb-free
HEAT**



MU92 Series

Single Color / Light Bar Module

Features

Light emitting surface (Outer size)	9 x 5 mm (9 x 5 mm) (L x W)								
Product features	<ul style="list-style-type: none"> • Single Color (Green, Yellow, Orange or Red) • Lead-free soldering compatible • RoHS compliant 								
Peak wavelength	<table> <tr> <td>Green</td> <td>: 555 nm</td> </tr> <tr> <td>Yellow</td> <td>: 570 nm</td> </tr> <tr> <td>Orange</td> <td>: 605 nm</td> </tr> <tr> <td>Red</td> <td>: 660 nm</td> </tr> </table>	Green	: 555 nm	Yellow	: 570 nm	Orange	: 605 nm	Red	: 660 nm
Green	: 555 nm								
Yellow	: 570 nm								
Orange	: 605 nm								
Red	: 660 nm								
Die materials	<table> <tr> <td>Green, Yellow</td> <td>: GaP</td> </tr> <tr> <td>Orange</td> <td>: GaAsP</td> </tr> <tr> <td>Red</td> <td>: GaAlAs</td> </tr> </table>	Green, Yellow	: GaP	Orange	: GaAsP	Red	: GaAlAs		
Green, Yellow	: GaP								
Orange	: GaAsP								
Red	: GaAlAs								
Soldering methods	TTW (Through The Wave) soldering and manual soldering								
Soldering methods	More than 2kV(HBM)								
Packing	Plastic bag								

Recommended Applications

Electric Household Appliances, OA/FA, Other General Applications

Color and Luminous Intensity

Part No.	Material	Emitted Color	Resin Color	Luminous Intensity I _v (mcd)			Number of Chips
				MIN.	TYP.	I _F	
MU92-5001	GaP	Green	Green	1.2	2.4	20	1
MU92-4001	GaP	Yellow	Yellow	3	6	20	1
MU92-3001	GaAsP	Orange	Orange	3	6	20	1
MU92-2001	GaAlAs	Red	Red	3	6	20	1

Absolute Maximum Ratings

(Ta=25°C)

Item	Symbol	Absolute Maximum Ratings				Unit
		5001	4001	3001	2001	
Power Dissipation	P _d	75	75	75	60	mW
Forward Current	I _F	30	30	30	30	mA
Pulse Forward Current ^{※1}	I _{FRM}	100	100	100	300	mA
Derating (Ta=25°C or higher)	ΔI _F	0.33	0.33	0.33	0.33	mA/°C
	ΔI _{FRM}	1.33	1.33	1.33	4.00	mA/°C
Reverse Voltage	V _R	4	4	4	4	V
Operating Temperature	T _{opr}	-30~+85				°C
Storage Temperature	T _{stg}	-30~+85				°C





 ※1 I_{FRM} Measurement condition : Pulse Width ≤ 1ms, Duty ≤ 1/20

Electro-Optical Characteristics





(Ta=25°C)

Item	Conditions	Symbol	Characteristics				Unit	
			5001	4001	3001	2001		
Forward Voltage	I _F =20mA	V _F	TYP.	2.2	2.1	2.2	1.7	V
			MAX.	2.5	2.5	2.5	2.0	
Reverse Current	V _R =4V	I _R	MAX.	100	100	100	100	μA
Peak Wavelength	I _F =20mA	λ _p	TYP.	555	570	605	660	nm
Spectral Line Half Width	I _F =20mA	Δλ	TYP.	30	30	30	30	nm





Technical Data(5001)







Technical Data(5001)







Technical Data(4001)







Technical Data(4001)







Technical Data(3001)







Technical Data(3001)



Technical Data(2001)




Technical Data(2001)



Package Dimensions

(Unit: mm)

(Tolerance : ± 0.25 mm)



TTW (Through The Wave) soldering Conditions

Pre-heating	100 °C 60 s	(MAX.) Resin surface temperature (MAX.)
Solder Bath Temp.	265 °C	(MAX.)
Dipping Time	5 s	(MAX.)
Position	At least 3.0 mm away from resin body	

- 1) The dip soldering process shall be 2 times maximum.
- 2) The product shall be cooled to normal temperature before the second dipping process.

Manual Soldering Conditions

Iron tip temp.	400 °C	(MAX.) (30 W Max.)
Soldering time and frequency	3 s 2 times	(MAX.) (MAX.)
Position	At least 3.0 mm away from resin body	

Reliability Testing Result

Reliability Testing Result	Applicable Standard	Testing Conditions	Duration	Failure
Room Temp. Operating Life	EIAJ ED-4701/100(101)	Ta = 25°C, If = Maximum Rated Current	1,000 h	0/10
Resistance to Soldering Heat	EIAJ ED-4701/300(302)	260±5°C, 3mm from package base	10sec	0/10
Temperature Cycling	EIAJ ED-4701/100(105)	Minimum Rated Storage Temperature(30min) ~Normal Temperature(15min) ~Maximum Rated Storage Temperature(30min) ~Normal Temperature(15min)	5 cycles	0/10
Wet High Temp. Storage Life	EIAJ ED-4701/100(103)	Ta = 60±2°C, RH = 90±5%	1,000 h	0/10
High Temp. Storage Life	EIAJ ED-4701/200(201)	Ta = Maximum Rated Storage Temperature	1,000 h	0/10
Low Temp. Storage Life	EIAJ ED-4701/200(202)	Ta = Minimum Rated Storage Temperature	1,000 h	0/10
Lead Tension	EIAJ ED-4701/400(401)	5N, 1time	10sec	0/10
Vibration, Variable Frequency	EIAJ ED-4701/400(403)	98.1m/s ² (10G), 100 ~ 2KHz sweep for 20min., XYZ each direction	2 h	0/10
Lead Bend	EIAJ ED-4701/400(401)	2.5N, 0°←→ 90°	2 times	0/10
Shock	JIS C 7201 A-8	It falls on wood engraving from height of 75cm.	3 times	0/10

Failure Criteria

Items	Symbols	Conditions	Failure criteria
Luminous Intensity	Iv	If=20mA	Testing Min. Value < Spec. Min. Value x 0.5
Forward Voltage	V _F	If=20mA	Testing Max. Value ≥ Spec. Max. Value x 1.2
Reverse Current	I _R	V _R =4V	Testing Max. Value ≥ Spec. Max. Value x 2.5
Cosmetic Appearance	-	-	No notable, decoloration, deformation and cracking

Special Notice to Customers Using the Products and Technical Information Shown in This Data Sheet

- 1) The technical information shown in the data sheets are limited to the typical characteristics and circuit examples of the referenced products. It does not constitute the warranting of industrial property nor the granting of any license.
- 2) For the purpose of product improvement, the specifications, characteristics and technical data described in the data sheets are subject to change without prior notice. Therefore it is recommended that the most updated specifications be used in your design.
- 3) When using the products described in the data sheets, please adhere to the maximum ratings for operating voltage, heat dissipation characteristics, and other precautions for use. We are not responsible for any damage which may occur if these specifications are exceeded.
- 4) The products described in the data sheets are made to be used in standard electronic applications such as office automation appliances, communication devices, audio visual, home appliances, and measuring instruments.
- 5) If the products in the data sheets are to be used for purposes other than the above which requires high level reliability and safety where failure and or malfunction of the product may cause death or other serious effects on the human body such as airplane, space activity, transportation, medical, nuclear), please contact our sales personnel.
- 6) In order to export the products or technologies described in this data sheet which are under the "Foreign Exchange and Foreign Trade Control Law," it is necessary to first obtain an export permit from the Japanese government.
- 7) No part of this data sheet may be reprinted or reproduced without prior written permission from Stanley Electric Co., Ltd.
- 8) The most updated edition of this data sheet can be obtained from the address below:
<http://www.stanley-components.com>