
PANJIT SEMI CONDUCTOR

MMBD4148TG

SURFACE MOUNT SWITCHING DIODES

VOLTAGE 100 Volts **POWER** 200mWatts

SOD-723 Unit: inch (mm)



FEATURES

- Fast switching Speed.
- Electrically Identical to Standerd JEDEC
- Surface Mount Package Ideally Suited for Automatic Insertion.
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

Case : SOD-723 plastic case.
Terminals : Solderable per MIL-STD-750,Method 2026
Approx. Weight : 0.0007gram
Marking Code : BH

ABSOLUTE RATINGS (T_A=25°C , unless otherwise noted)

PARAMETER	SYMBOL	MMBD4148TG	UNITS
Reverse Voltage	V_R	75	V
Peak Reverse Voltage	V_{RRM}	100	V
RMS Voltage	V_{RMS}	50	V
Maximum DC Blocking Voltage	V_{DC}	75	V
Maximum Average Forward Current at T_A=25 °C	$I_{F(AV)}$	150	mA
Peak Forward Surge Current, 0.001ms	I_{FSM}	4	A
Power Dissipation Derate Above 25 °C	P_{TOT}	200	mW
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-55 to 150	°C

THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	MMBD4148TG	UNITS
Typical Thermal Resistance	$R_{\theta JA}$	635	°C / W

NOTE:
1. CJ at V_R=0, f=1MHZ
2.From I_F=10mA to I_R=1mA, V_R=6Volts, R_L=100Ω

MMBD4148TG

ELECTRICAL CHARACTERISTICS (T_A=25°C , unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	VALUE	UNITS
Maximum Forward Voltage	V_F	I_F=1mA I_F=10mA I_F=50mA I_F=150mA	0.715 0.855 1.00 1.25	V
Reverse Leakage Current	I_R	V_R=20V V_R=75V	0.025 2.5	μA
Maximum Total Capacitance	C_T	V_R=0V, f=1MHz	1.5	pF
Maximum Reverse Recovery Time	t_{rr}	I_F=10mA,I_R=1mA V_R=6V,R_L=100Ω	4	ns




FIG. 1-TYPICAL FORWARD CHARACTERISTIC




FIG. 2-TYPICAL REVERSE CHARACTERISTICS




FIG. 3 TYPICAL JUNCTION CAPACITANCE





FIG. 4 POWER DERATING CURVE

MMBD4148TG

MOUNTING PAD LAYOUT

SOD-723 Unit: inch (mm)



ORDER INFORMATION

- Packing information

  T/R - 8K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2009

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.