


Servo motor EMMS-AS-40-MK-LS-SRB

Part number: 1578624

FESTO



Data sheet

| Feature | Value |
|--|--|
| Number of pole pairs | 4 |
| Type code | EMMS-AS |
| Rotor position sensor | Resolver |
| Rotor position sensor interface | SIN/COS analog signals |
| Rotor position sensor measuring principle | Inductive |
| Temperature monitoring | PTC resistor |
| Max. rotational speed | 11520 1/min |
| Nominal rotary speed | 10300 1/min |
| Brake DC operating voltage | 24 V |
| Insulation protection class | F |
| Brake power consumption | 6.2 W |
| Motor constants | 0.344 Nm/A |
| Nominal operating voltage DC | 360 V |
| Motor nominal power | 232 W |
| DC nominal voltage | 360 V |
| Motor nominal current | 0.63 A |
| Phase-phase winding resistance | 31 Ohm |
| Winding inductance phase-phase | 10.4 mH |
| Type of winding switch | Star inside |
| Peak current | 3.3 A |
| Voltage constant, phase-to-phase | 22.1 mVmin |
| Rating class according to EN 60034-1 | S1 |
| CE marking (see declaration of conformity) | As per EU EMC directive As per EU low voltage directive |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| Storage temperature | -20 °C ... 60 °C |
| Relative air humidity | 0 - 90 % |
| Degree of protection | IP54 |
| Ambient temperature | -40 °C ... 40 °C |
| Certification | RCM compliance mark c UL us - Recognized (OL) |
| Total output inertia moment | 0.059 kgcm ² |
| Brake holding torque | 0.4 Nm |
| Brake mass moment of inertia | 0.01 kgcm ² |
| Nominal torque | 0.22 Nm |
| Peak torque | 1 Nm |

| Feature | Value |
|----------------------------------|--|
| Stall torque | 0.26 Nm |
| Permissible axial shaft load | 12 N |
| Permissible radial shaft load | 82 N |
| MTTF, subcomponent | 80 years, rotor position sensor 4469 years, holding brake |
| MTTFd, subcomponent | 160 years, rotor position sensor |
| Switching cycles, holding brake | 5 million idle actuations (without friction work!) |
| Product weight | 740 g |
| Electrical connection technology | Plug |
| Note on materials | RoHS-compliant |
| Conforms to standard | IEC 60034 |
| Featherkey shaft design | DIN 6885 A 2 x 2 x 10 |