


935133424510-xxN

In Production

Appearance & Shape



Features

- | Extended operating temperature range (up to 250°C) with low capacitance variation.
- | High stability.
- | High reliability.
- | Low leakage current.
- | Verylow ESR and ESL.

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

935133424510-xxN



Specifications

| | |
|--|------------------|
| Series | XTSC |
| Applications | High Reliability |
| Features | High Temperature |
| Mounting Method | Solder Mounted |
| Operating Temperature Range | -55°C to 250°C |
| Size Code (in inch) | 0402 |
| L x W (size) | 1.20 x 0.70mm |
| Breakdown Voltage (For the rated voltage, please see the FAQ.) | 11Vdc |
| Capacitance | 10nF |
| Thickness | 400µm |

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.