



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1000V AC/minute
- 7、Material: Wafer LCP、PA6T、UL94V-0
PIN Brass Tin-plated
Solder tad Phosphoric bronze Tin-plated

编 号	尺寸 (mm)		
	A	B	C
HC-HA-2ALT	2.50	10.00	7.50
HC-HA-3ALT	5.00	12.50	10.00
HC-HA-4ALT	7.50	15.00	12.50
HC-HA-5ALT	10.00	17.50	15.00
HC-HA-6ALT	12.50	20.00	17.50
HC-HA-7ALT	15.00	22.50	20.00
HC-HA-8ALT	17.50	25.00	22.50
HC-HA-9ALT	20.00	27.50	25.00
HC-HA-10ALT	22.50	30.00	27.50
HC-HA-11ALT	25.00	32.50	30.00
HC-HA-12ALT	27.50	35.00	32.50

GENERAL TOLERANCE		制 图 DRAWING 2017、06、01	料 号 PART NO.	HC-HA-NALT		版 本 REV.	A
X.±0.25	X.*±2'		品 名 TITLE	HA立贴 WAFER SMT TYPE		页 次 SHEET	1/1
.X±0.20	.X*±1'		审 核 CHECK	客 户 料 号 CUTL NO.			
.XX±0.15	.XX*±0.5'		核 准 APPROVAL				
.XXX±0.10	.XXX*±0.5'	单 位 UNITS	MM	比 例 SCALE	1:1	深 圳 市 华 灿 天 禄 电 子 有 限 公 司	