

REV. B  
DCO 300860



TOLERANCES  $\pm .010"$  - UNLESS OTHERWISE SPECIFIED

|   |                            |
|---|----------------------------|
| COIL: @ 25°C                            |                            |
| RESISTANCE                              | 320 OHMS $\pm 10\%$        |
| NOMINAL VOLTAGE                         | 28 VDC                     |
| MUST OPERATE                            | 13.5 VDC MAX.              |
| COIL TRANSIENT SUPPRESSION: 42 VDC MAX. |                            |
| MUST RELEASE                            | 5.5 VDC MAX., 2.3 VDC MIN. |

|              |                           |
|--------------|---------------------------|
| ENVIRONMENT: |                           |
| VIBRATION    | 10 Hz TO 3000 Hz @ 30 g's |
| SHOCK        | 200 g's 6 MS. DURATION    |
| TEMPERATURE  | -70 °C TO +125 °C         |

NOTES: OPERATE, RELEASE 10 MS MAX.  
CONTACT BOUNCE 1 MS MAX.  
CONTACT BREAK BOUNCE 0.1 MS MAX.

CUSTOMER DATA SHEET



TERMINAL VIEW

|  |  |
|--|--|
| CONTACT RATING:                          |  |
| 25 AMPS 28 VDC, 115 VAC 400 Hz RESISTIVE |  |
| 50,000 OPERATIONS                        |  |

DR. B.D. 21MAY2008 CK. J.M.B. 5/21/08

**Tyco Electronics** ©COPYRIGHT 2005  
TYCO ELECTRONICS CORPORATION  
ALL INTERNATIONAL RIGHTS RESERVED

CUST. QPL  
CUST. NO. M6106/19-024 REV. ----

TE NUMBER  
3-1617748-0

CII PART NUMBER  
FCA-125-24