

Part Number: C9413A

Revision Date: 9/11/2012

4PR 22 AWG 7/30 TC PVC / OAS / PVC



A. CONSTRUCTION

Conductor: #22 AWG 7/30 Tinned Copper
 Insulation: .010" Polyvinyl Chloride (PVC)
 Pairing: Twin 2/C @ 1.50" LHL
 Cable Core: Cable 4/pr @ 3.25" LHL w/ clear polyester wrap
 Shield: 22AWG 7/30 TC Drain wire, Aluminum / Polyester foil facing in, 100% coverage
 Jacket: .032" Polyvinyl Chloride (PVC) jacket
 Ripcord under Jacket"
CAROL® EXZEL™ -- C9413A -- 4PR 22 AWG SHIELDED E105765-H (UL) TYPE CM 105C OR AWM 2464 80C 300V VW-1 --- LL69381 CSA TYPE CMG 105C FT4 -- CE -- -- ROHS -- MADE IN USA (DATE CODE) (TRUMARK SEQUENTIAL FOOTAGE)
 Print Legend:

DIAMETERS

.029" Nom
 .049" Nom
 .223" Nom
 .287" Nom

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	CM/CMG: 105C, AWM: 80C
Suggested Working Voltage:	300V
Conductor DCR:	16.89 Ohms/M' @ 20°C
Mutual Capacitance:	27.5 pF/ft. @ 1 kHz

D. COLOR CODE

ITEM	COLOR
1	WHITE / BLACK
2	WHITE / BROWN
3	WHITE / RED
4	WHITE / ORANGE