

Han Q 5/0 HighTemp-M-c



Image is for illustration purposes only. Please refer to product description.

Part number	09 12 805 3004
Specification	Han Q 5/0 HighTemp-M-c
HARTING eCatalogue	https://b2b.harting.com/09128053004

Identification

Category	Inserts
Series	Han [®] Q High Temp
Identification	5/0

Version

Termination method	Crimp termination
Gender	Male
Size	3 A
With wire protection	0
Number of contacts	5
PE contact	1
Details	Please order crimp contacts separately. Coding pins on request

Technical characteristics

Conductor cross-section	[0,14] ... [2,5 mm ²]
Rated current	16 A
Rated voltage conductor-earth	230 V
Rated voltage conductor-conductor	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Insulation resistance	>10 ¹⁰ Ω



Pushing Performance

Technical characteristics

Limiting temperature [-40] ... [+200 °C] With Han® High Temp components

Mating cycles ≥500

Material properties

Material (insert) Liquid crystal polymer (LCP)

Colour (insert) Black

Material flammability class acc. to UL 94 V-0

Specifications and approvals

Specifications EN 60664-1
IEC 61984

CE 0

Commercial data

Packaging size 10

Net weight 15 g

Country of origin Romania

European customs tariff number 85389099

eCl@ss 27440205 Contact insert for industrial connectors