



FSA2367 — Low R_{ON} (0.75 Ω) Triple-SPDT, Negative-Swing Audio Source Switch

Features

- 10 μ A Maximum I_{CCT} Current Over Expanded Control Voltage Range ($V_{IN}=2.6V$, $V_{CC}=4.3V$)
- On Capacitance 55pF Typical (C_{ON})
- 0.75 Ω Typical On Resistance (R_{ON})
- Common Ports 1A, 2A, 3A with Negative Swing Audio to -2V
- -3db Bandwidth: > 150 MHz
- Low Power Consumption (1 μ A Maximum)
- Power-Off Feature for 1A/2A/3A Pin ($I_{IN} < 2\mu A$)
- Packaged in Pb-Free 14-Pin TSSOP and DQFN

Applications

- Cell Phone, PDA, Digital Camera, and Notebook
- LCD Monitor, TV, and Set-Top Box

Description

The FSA2367 is a triple Single-Pole Double-Throw (SPDT) switch that multiplexes three sources of data or audio under independent control pins. The FSA2367 has special circuitry on the 1A, 2A, 3A pins that allows a power-off feature. With the V_{CC} supply removed and a voltage on the 1A/2A/3A pins, there is minimal leakage current into the 1A/2A/3A data pins. In addition, the FSA2367 also features very low quiescent current to extend battery life. The low quiescent current allows mobile handset applications direct interface with the baseband processor general-purpose I/Os. Typical applications involve switching in portables and consumer applications such as cell phones, digital cameras, and notebooks with hubs or controllers.

IMPORTANT NOTE:

For additional performance information, please contact analogswitch@fairchildsemi.com.

Ordering Information

Part Number	Top Mark	Pb-Free	Package
FSA2367BQX	2367	Yes	14-Terminal Depopulated very thin Quad Flat-pack No leads (DQFN) 2.5 x 3.0mm, JEDEC MO-241
FSA2367MTCX	FSA2367	Yes	14-Lead Thin Shrink Small Outline Package (TSSOP), 4.4mm Wide, JEDEC MO-153

Analog Symbol




Figure 1. Analog Symbol

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE [®]	HiSeC [™]	Programmable Active Droop [™]	TinyPower [™]
Across the board. Around the world. [™]	<i>i-Lo</i> [™]	QFET [®]	TinyWire [™]
ActiveArray [™]	ImpliedDisconnect [™]	QS [™]	TruTranslation [™]
Bottomless [™]	IntelliMAX [™]	QT Optoelectronics [™]	μSerDes [™]
Build it Now [™]	ISOPLANAR [™]	Quiet Series [™]	UHC [®]
CoolFET [™]	MICROCOUPLER [™]	RapidConfigure [™]	UniFET [™]
CROSSVOLT [™]	MicroPak [™]	RapidConnect [™]	VCX [™]
CTL [™]	MICROWIRE [™]	ScalarPump [™]	Wire [™]
Current Transfer Logic [™]	MSX [™]	SMART START [™]	
DOMET [™]	MSXPro [™]	SPM [®]	
E ² CMOS [™]	OCX [™]	SuperFET [™]	
EcoSPARK [®]	OCXPro [™]	SuperSOT [™] -3	
EnSigna [™]	OPTOLOGIC [®]	SuperSOT [™] -6	
FACT Quiet Series [™]	OPTOPLANAR [®]	SuperSOT [™] -8	
FACT [®]	PACMAN [™]	TCM [™]	
FAST [®]	POP [™]	The Power Franchise [®]	
FASTr [™]	Power220 [®]	 [™]	
FPS [™]	Power247 [®]	TinyBoost [™]	
FRFET [®]	PowerEdge [™]	TinyBuck [™]	
GlobalOptoisolator [™]	PowerSaver [™]	TinyLogic [®]	
GTO [™]	PowerTrench [®]	TINYOPTO [™]	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS**Definition of Terms**

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild Semiconductor. The datasheet is printed for reference information only.

Rev. I23