
Shielded Drum Core Inductor

PA4302.XXXNLT Series




- **Height:** 5.6mm Max
- **Footprint:** 7.5 x 7.5 mm Max
- **Current Range:** 0.5A to 7.5A
- **Inductance Range:** 1uH to 330uH

Electrical Specifications @ 25°C — Operating Temperature -40°C to 125°C			
Pulse Part Number	**Inductance (uH)**	**Rated Current (A) Max**	**DC Resistance (mΩ) Max**
PA4302.102NLT	1.0	7.5	20
PA4302.332NLT	3.3	5.6	22.8
PA4302.472NLT	4.7	4.8	26.8
PA4302.682NLT	6.8	4	36.8
PA4302.103NLT	10	3	55
PA4302.473NLT	47	1.45	185
PA4302.683NLT	68	1.2	265
PA4302.104NLT	100	1	380.5
PA4302.224NLT	220	0.72	765
PA4302.334NLT	330	0.5	1344

Mechanical


Schematic

PA4302.XXXNLT




FINAL OUTLINE

SUGGESTED PAD LAYOUT



Part Number	A (max)	B (max)	C	D	E	F	G	H
PA4302.XXXNLT	7.5 MAX	5.6 MAX	(2.0)	(7.2)	(5.0)	(2.3)	(1.6)	(4.8)

TAPE & REEL INFO



SURFACE MOUNTING TYPE, REEL/TAPE LIST

TYPE	REEL SIZE (mm)				TAPE SIZE (mm)									QTY
	A	B	G	N	E	F	D0	P	P0	P2	W	T	K0	PCS/REEL
PA4302.XXXNLT	0330	21	16.5	100	1.75	7.5	1.5	12	4	2	16	0.40	5.6	900

NOTES:

1. Inductance tolerance is +/-30% for inductance values between 1uH and 6.8uH and +/-20% for values between 10uH and 330uH.
2. Inductance is measured at 100kHz, 250mV
3. The rated current as listed is the rms or heating current that the part can withstand with acceptable temperature rise in typical applications. At the listed current the inductance typically drops to 85-90% of the no load value when measured at 25C.
4. The temperature of the component (ambient plus temperature rise) must be within the stated operating temperature.

For More Information

Pulse Worldwide Headquarters
12220 World Trade Drive
San Diego, CA 92128
U.S.A.

Tel: 858 674 8100
Fax: 858 674 8262

Pulse Europe
Zeppelinstrasse 15
71083 Herrenberg
Germany

Tel: 49 7032 7806 0
Fax: 49 7032 7806 12

Pulse China Headquarters
B402, Shenzhen Academy of Aerospace Technology Bldg.
10th Kejinan Road
High-Tech Zone
Nanshan District
Shenzhen, PR China 518057
Tel: 86 755 33966678
Fax: 86 755 33966700

Pulse North China
Room 2704/2705
Super Ocean Finance Ctr.
2067 Yan An Road West
Shanghai 200336
China

Tel: 86 21 62787060
Fax: 86 2162786973

Pulse South Asia
135 Joo Seng Road
#03-02
PM Industrial Bldg.
Singapore 368363

Tel: 65 6287 8998
Fax: 65 6287 8998

Pulse North Asia
3F, No. 198
Zhongyuan Road
Zhongli City
Taoyuan County 320
Taiwan R. O. C.
Tel: 886 3 4356768
Fax: 886 3 4356823 (Pulse)
Fax: 886 3 4356820 (FRE)

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2014. Pulse Electronics, Inc. All rights reserved.