

# Antenna - RAD-ISM- 900-ANT-OMNI-0-N - 5604160

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Omnidirectional antenna, 900 MHz, gain: 2 dBi, polarization: linear, opening angle: h 360°, connection: N (female), incl. mounting bracket for wall mounting

## Your advantages

- For freely mobile applications
- For multipoint or mesh connections

## Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 288743
GTIN	4046356288743

## Technical data

### Dimensions

Height	88.9 mm
Diameter	3.175 mm
Fixed cable length	3.00 in.

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 75 °C
---------------------------------	------------------

### General

Frequency range	900 MHz 890 MHz ... 960 MHz
Horizontal beamwidth	360 °
Polarization	Linear vertical
Impedance	50 Ω
Gain	2.15 dBi
Connection method	Type N (female)

# Antenna - RAD-ISM- 900-ANT-OMNI-0-N - 5604160

## Technical data

### General


Cable type	RG-58
Fixed cable length	3.00 in.
Material	V2A (Antenna housing)
	V2A (Bracket)
Mounting type	Wall mounting

### Environmental Product Compliance


China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Drawings

Schematic diagram



Schematic diagram



Installation example