



NOTES.

1. FOR USE WITH BELDEN 5422 CABLE.
2. SAME AS 1965-3 EXCEPT FOR FINISH.
3. FOR CABLING INSTRUCTIONS SEE C-59-315-1.

UNLESS OTHERWISE SPECIFIED:

- | | |
|--|---|
| <ol style="list-style-type: none"> 1. TOLERANCES:
FRACTIONS ± .010 DECIMALS ± .004 ANGLES ± 0° 30' T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES. | <ol style="list-style-type: none"> 2. REMOVE ALL BURRS. BREAK SHARP EDGES .003 MAX. 3. NO FILLETS PERMITTED. 4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX. 5. ALL DIMENSIONS PRIOR TO PLATING. |
|--|---|

17	1	INSULATOR	C-59-187-4-M99
16	1	BAYONET SLEEVE	
15	1	INSULATOR	C-59-187-3-M99
14	1	OUTER CONTACT	C-59-187-2-M99
13	1	BNC CONTACT M	1-4896-3MA9
12	1	GASKET	
11	1	SPRING WASHER	
10	1	CAM LEVER	
7	1	INSULATOR	C-59-187-5-M99
6	1	RETAINER	1-1119-1M06
5	1	BRAID CLAMP	631-5-M06
4	1	GASKET	631-6-M99
3	1	WASHER	260C-1-M06
2	1	BODY	C-59-166-6-M06
1	1	CLAMP NUT	631-4-M06
ITEM REQD		DESCRIPTION	DWG NO

REVISIONS

ISSUE	CHANGES
0	ER 10818 NLA 24 FEB 72
1	CN 159184 GA 15 JUL 76
2	CN 25083 C SL 1 SEP 83
3	CN 34639 C KH 17 MAY 93
4	CN 35740 A KH 12 AUG 94

1965-3-9 S.D

S-D

**BNC TRIAX
PLUG**

DRAWN NLA DATE 23 FEB 72
APP'D J.M. DATE 24 FEB 72

KINGS ELECTRONICS
40 HANBLEDALE ROAD
TUCKAHOE, N. Y.

1965-3-9 S.D