

## Ring cable lug - C-RCEI 6/M5 - 3241211

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ring cable lug, yellow, 4 ... 6 mm<sup>2</sup>, M5, with copper sleeve incorporated, for insulation crimp

### Product Features

- The sleeves are conically tapered to facilitate easy and correct insertion of the conductor
- The mechanical load capacity of the connection is significantly increased by the additionally applied copper sleeve (insulation crimp).



### Key Commercial Data

|                        |          |
|------------------------|----------|
| Packing unit           | 1 pc     |
| Minimum order quantity | 100 pc   |
| Custom tariff number   | 85369010 |
| Country of origin      | Taiwan   |

### Technical data

#### Dimensions

|   |        |
|---|--------|
| Length (b)  | 26 mm  |
| Width (a)   | 9.5 mm |
| Length of insulation sleeve (c)                           | 13 mm  |
| Inner dimension of the insulating collar (d)              | 6.5 mm |
| Distance between the center and the insulation sleeve (e) | 8.3 mm |
| Inner diameter (f)  | 5.3 mm |
| Material thickness (g)                                    | 1 mm   |

#### Ambient conditions

|   |   |
|---|---|
| Ambient temperature (operation)                 | -20 °C ... 105 °C   |
| Ambient temperature (assembly)                  | -20 °C ... 100 °C   |
| Optimum ambient temperature (storage/transport) | 20 °C 50 % Humidity (RH), store inside sealed original packaging. Avoid direct sunlight and heat. |

# Ring cable lug - C-RCEI 6/M5 - 3241211

## Technical data

### Ambient conditions

|                        |        |
|------------------------|--------|
| Short-term temperature | 100 °C |
|------------------------|--------|

### General

|  |              |
|--|--------------|
| Color                                  | yellow       |
| Components                             | Halogen-free |
| Flammability rating according to UL 94 | V2           |
| Material                               | Copper       |
| Insulating material                    | PA           |
| Coating                                | Tin-plated   |

### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V2 |
|--|----|

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400204 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC001052 |
| ETIM 5.0 | EC001052 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212109 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |
| UNSPSC 13.2   | 27121703 |

## Approvals

### Approvals

# Ring cable lug - C-RCEI 6/M5 - 3241211

## Approvals

Approvals

EAC

---

Ex Approvals

---

Approvals submitted

---

## Approval details

|     |
|-----|
| EAC |
|-----|

## Drawings

Dimensional drawing

