Features

- BV_{CEO} > 20V
- I_C = 6.5A Continuous Collector Current
- Very Low Saturation Voltage $V_{CE(sat)}$ < 30mV @ 1A
- $R_{CE(sat)}$ = 18mΩ
- High h_{FE} Min 260 @ 2A
- 1.5W Power Dissipation
- High Forward Blocking Voltage
- Complementary PNP Type: ZXTP19020DFF
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 and 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Case: SOT23F
- Case Material: Molded Plastic. "Green" Molding Compound UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 e3
- Weight: 0.012 grams (Approximate)

Description

Advanced process capability has been used to maximize the performance of this transistor. The SOT23F package is compatible with the industry standard SOT23 footprint but offers lower profile and higher dissipation for applications where power density is of utmost importance.


Applications

- MOSFET and IGBT Gate Drivers
- LED Driver
- Strobe Flash
- Motor Drive
- Micro Buffers


SOT23F



Top View



Device Symbol



Top View
Pin Configuration


Ordering Information (Note 4)

Part Number	Compliance	Marking	Reel size (inches)	Tape width (mm)	Quantity per reel
ZXTN19020DFFTA	AEC-Q101	1E3	7	8	3,000

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
2. See http://www.diodes.com/quality/lead_free.html for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at http://www.diodes.com/products/packages.html.

Marking Information

SOT23F



1E3 = Product Type Marking Code
YW = Date Code Marking
Y = Year : 0~9
W = Week : A~Z : 1~26
a~z : 27~52
z represents 52 & 53 week

© Diodes Incorporated

Absolute Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	70	V
Collector-Emitter Voltage (Forward Blocking)	V_{CEX}	70	V
Collector-Emitter Voltage	V_{CEO}	20	V
Emitter-Collector Voltage (Reverse Blocking)	V_{ECO}	4.5	V
Emitter-Base Voltage	V_{EBO}	7	V
Continuous Collector Current	I_C	6.5	A
Peak Pulse Current	I_{CM}	20	A
Base Current	I_B	1	A

Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Power Dissipation Linear Derating Factor	(Note 5)	P_D	0.84 6.72	W mW/°C
	(Note 6)		1.34 10.72	
	(Note 7)		1.50 12.0	
	(Note 8)		2.0 16.0	
Thermal Resistance, Junction to Ambient	(Note 5)	$R_{\theta JA}$	149	°C/W
	(Note 6)		93	
	(Note 7)		83	
	(Note 8)		60	
Thermal Resistance, Junction to Lead	(Note 9)	$R_{\theta JL}$	43.77	°C/W
Operating and Storage Temperature Range		T_J, T_{STG}	-55 to +150	°C


ESD Ratings (Note 10)

Characteristic	Symbol	Value	Unit	JEDEC Class
Electrostatic Discharge - Human Body Model	ESD HBM	4,000	V	3A
Electrostatic Discharge - Machine Model	ESD MM	400	V	C


Notes:
5. For a device mounted with the exposed collector pad on 15mm x 15mm 1oz copper that is on a single-sided 1.6mm FR-4 PCB; device is measured under still air conditions whilst operating in a steady-state.
6. Same as Note 5, except the device is mounted on 25mm x 25mm 2oz copper.
7. Same as Note 5, except the device is mounted on 50mm x 50mm 2oz copper.
8. Same as Note 7, whilst measured at t < 5 seconds.
9. Thermal resistance from junction to solder-point (at the end of the collector lead).
10. Refer to JEDEC specification JESD22-A114 and JESD22-A115.

© Diodes Incorporated


Thermal Characteristics and Derating Information




Safe Operating Area




Safe Operating Area



Transient Thermal Impedance



Pulse Power Dissipation



Derating Curve

© Diodes Incorporated


Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS						
Collector-Base Breakdown Voltage	BV_{CBO}	70	100	—	V	I_C = 100µA
Collector-Emitter Breakdown Voltage (Forward Blocking)	BV_{CEX}	70	100	—	V	I_C = 100µA; R_{BC} < 1kΩ or -1V < V_{BE} < 0.25V
Collector-Emitter Breakdown Voltage (Base Open) (Note 11)	BV_{CEO}	20	30	—	V	I_C = 10mA
Emitter-Base Breakdown Voltage	BV_{EBO}	7	8.4	—	V	I_E = 100µA
Emitter-Collector Breakdown Voltage (Reverse Blocking)	BV_{ECX}	6	8.4	—	V	I_E = 100µA; R_{BC} ≤ 1kΩ or -0.25V < V_{BC} < 0.25V
Emitter-Collector Breakdown Voltage (Base Open)	BV_{ECO}	4.5	5.7	—	V	I_E = 100µA
Collector-Base Cut-Off Current	I_{CBO}	— —	<1 —	50 20	nA µA	V_{CB} = 56V V_{CB} = 56V, T_A = +100°C
Collector-Emitter Cut-Off Current	I_{CEX}	—	—	100	nA	V_{CE} = 56V; R_{BE} ≤ 1kΩ or -1V < V_{BE} < 0.25V
Emitter-Base Cut-Off Current	I_{EBO}	—	<1	50	nA	V_{EB} = 5.6V
ON CHARACTERISTICS (Note 11)						
Static Forward Current Transfer Ratio	h_{FE}	300 260 160 50	450 420 270 80	900 — — —	—	I_C = 0.1A, V_{CE} = 2V I_C = 2A, V_{CE} = 2V I_C = 6.5A, V_{CE} = 2V I_C = 15A, V_{CE} = 2V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	—	25 45 70 55 140	30 65 95 75 190	mV	I_C = 1A, I_B = 100mA I_C = 1A, I_B = 10mA I_C = 2A, I_B = 20mA I_C = 2A, I_B = 40mA I_C = 6.5A, I_B = 180mA
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	—	940	1050	mV	I_C = 6.5A, I_B = 180mA
Base-Emitter On Voltage	$V_{BE(on)}$	—	830	950	mV	I_C = 6.5A, V_{CE} = 2V
SMALL SIGNAL CHARACTERISTICS						
Transition Frequency	f_T	—	160	—	MHz	I_C = 50mA, V_{CE} = 5V, f = 50MHz
Input Capacitance	C_{ibo}	—	297	—	pF	V_{EB} = 0.5V, f = 1MHz
Output Capacitance	C_{obo}	—	32.6	40	pF	V_{CB} = 10V, f = 1MHz
Delay Time	t_d	—	129	—	ns	V_{CC} = 10V, I_C = 1A, I_{B1} = -I_{B2} = 10mA
Rise Time	t_r	—	96	—	ns	
Storage Time	t_s	—	398	—	ns	
Fall Time	t_f	—	90	—	ns	


Note: 11. Measured under pulsed conditions. Pulse width ≤ 300µs. Duty cycle ≤ 2%.

© Diodes Incorporated


Typical Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)




$V_{CE(SAT)}$ v I_C




$V_{CE(SAT)}$ v I_C



h_{FE} v I_C



$V_{BE(SAT)}$ v I_C




$V_{BE(ON)}$ v I_C

© Diodes Incorporated

Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT23F




SOT23F			
Dim	**Min**	**Max**	**Typ**
A	0.80	1.00	0.90
A1	0.00	0.10	0.01
b	0.35	0.50	0.44
c	0.10	0.20	0.16
D	2.80	3.00	2.90
e	0.95 REF		
e1	1.90 REF		
E	2.30	2.50	2.40
E1	1.50	1.70	1.65
k	1.20	-	-
L	0.30	0.65	0.50
L1	0.30	0.50	0.40
R	0.05	0.15	-
All Dimensions in mm			

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT23F



Dimensions	Value (in mm)
C	0.95
X	0.80
Y	1.110
Y1	3.000

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2016, Diodes Incorporated

www.diodes.com