Power cable - PLD E 608-CA-MS/4,0/FS AM - 2702305

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Power cable, 3-position, PVC, orange RAL 2004, Plug straight, black, on Socket straight, black, cable length: 4 m

Product Description

The cable serves to connect multiple 600 class PLD enclosure lights in series.

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 113302
GTIN	4055626113302

Technical data

Dimensions

Length of cable	4 m

Ambient conditions

Degree of protection	IP20
	IP40 (plugged in)

General

Rated current at 40°C	16 A
Rated voltage	250 V AC
Number of positions	3
Coding	black
Insertion/withdrawal cycles	100

Material

Material, knurls	not available

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e

Power cable - PLD E 608-CA-MS/4,0/FS AM - 2702305

Technical data

Environmental Product Compliance

	No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com