





A



B



C



D

Material:



- Housing: PC UL94V-0
- Insert Material: PBT+20%GF UL94V-0
- PCB Material: FR-4 (Thickness 1.6MM)
- Contact Material: Phosphor Bronze Stamp Pin T=0.50MM
- IDC Contact Material: Phosphor Bronze 50μ" Gold T=0.50MM

E

Electrical:

- Voltage Rating: 125V AC RMS
- Current Rating: 1.5 AMP
- Contact Resistance: 100MΩ Max.
- Insulation Resistance: 1,000MΩ Min. @ 500V DC
- Dielectric Strength: 750V AC RMS 60Hz, 1 Min.

F



Environmental:

- Storage: -40°C ~ +85°C
- Operational Temperature: 0°C ~ +70°C
- Conform to TIA/EIA 568 B.2-1
- Mates with modular plug conforming to FCC part 68, Subpart F

G

Scale	1:1						Name	Item No. A-TA3534-R
TOLERANCE					Drawn	12.20.11	Chappell	
X.X	±0.40				Approved			Title Keystone Jack Cat5e, 50μ", RJ45 <=> RJ45, F-Thru Slim Style, Black
X.XX	±0.25							Drawing No.
X.XXX	±0.15							rev00
Angle	±3°							
								Replace
								Sheet

