



Nut Torque: 5 ~ 14Nm  
 Operating Pressure: 300gf ±100gf  
 Operating Stroke: 3.0mm±0.3  
 Protection Grade: IP65, IK08  
 Function: ON-OFF  
 Contact: Silver Alloy  
 Base: PA66  
 Shell: Brass, Ni Plating  
 Button: SUS  
 Lamp Type: LED  
 Lamp Life: 50000H  
 Forward current : 20mA  
 Rating: 3A 250V AC  
 Contact Resistance: 50mΩ MAX.  
 Insulation Resistance: 100MΩ MIN.  
 Dielectric Strength: 1500VAC 1 minute  
 Electrical life: 50,000 cycles  
 Mechanical life : 100,000 cycles  
 Operating Temperature: -20°C~80°C  
 Safety Approval:

公差 TOLERANCES .X±0.5 .XX±0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.



版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECON NO.	核准 APPROVED BY	核对 CHECKED BY	绘图 DRAWN BY	品名 TITLE	图号 DRAWING NO
				A0	1:1	孙成	PBM-19Z15-FS-G1-R220-B8S-A3	PBM-19Z15-FS-G1-R220-B8S-A3_A0