

**42051**

**5 A FIXED THREE TERMINAL  
NEGATIVE VOLTAGE REGULATORS**  
Commercial or Military

**Mii**

HYBRID MICROELECTRONICS  
PRODUCTS DIVISION

**Features:**

- Output current to 5 Amps
- Output voltage To -34 V
- Internal short circuit protection

**Applications:**

- Military and Hi Rel industrial applications where hermetically sealed product is required.

**DESCRIPTION**

The 42051 series of regulators covers the voltage range from -5 V through -34 V. These regulators are fabricated using hybrid techniques. The devices are complete with internal short circuit protection which includes voltage shutdown and current fold-back. To insure circuit stability under all load combinations it is recommended that a minimum of 2.0  $\mu$ F capacitance (solid tantalum) be connected between power ground and the input to the regulator.

**ABSOLUTE MAXIMUM RATINGS**

Output Current - $I_{OUT}$ .....	5 A
Power Dissipation @ 25°C Case Temperature .....	120W
Operating Temperature .....	-55°C to +125°C
Storage Temperature .....	-65°C to +150°C
Input Voltage - $V_{IN}$ .....	-40 V

NOTE: Lead Temperature (Soldering, 10 sec.) 300°C

**Micropac Industries** cannot assume any responsibility for any circuits shown or represent that they are free from patent infringement.  
**Micropac** reserves the right to make changes at any time in order to improve design and to supply the best product possible.

## ELECTRICAL CHARACTERISTICS (Note 1)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	$V_{OUT}$	$I_{OUT} = 1A, V_{IN} = V_O - 5V$	$V_{OUT} + .1V$	$V_{OUT}$	$V_{OUT} - .1V$	VDC
Differential Voltage $V_{IN} - V_{OUT}$	$\Delta V$	$I_{OUT} = I_{MAX}$	5			VDC
Line Regulation (Note 3)		$-V_{IN} = V_{OUT} - 5V$ to $-V_{IN} = -40V$			.1	% $V_{OUT}$
Load Regulation (Note 2)		$I_{OUT} = .25A$ to $-I_{OUT} = -I_{MAX}$ $V_{IN} = V_O - 5V$			40	mV
Ripple Rejection		$f = 50$ to $500$ Hz 1.0V (P-P) $V_{IN} - V_{OUT} = 5V$	50			dB
Temperature Coefficient	$T_C$	$0^\circ C \leq T_C \leq 100^\circ C$		.05		%/ $^\circ C$
Standby Current	$I_S$				25	mA
Thermal Resistance	$\theta_{JC}$			1		$^\circ C/W$
Long Term Stability				0.1		%/1000 hrs

Note 1: Case temperature 25°C unless otherwise specified.

Note 2: Voltage measured at Pin 2 within .05 inches from case.


Note 3: Instantaneous regulation, average chip temperature changes must be accounted for separately.

## Standard Outputs

TYPE	$V_{OUT}$ (VDC)	MAX $I_{OUT}$ (A)	TYP $I_{KNEE}$ (A)	TYP $I_{SC}$ (A)
42051 - 055	-5	5	6.5	2.5
065	-6	5	6.5	2.5
075	-7	5	6.5	2.5
085	-8	5	6.5	2.5
095	-9	5	6.5	2.5
105	-10	5	6.5	2.5
124	-12	4	5	2.5
144	-14	4	5	2
154	-15	4	5	2
164	-16	4	5	2
184	-18	4	5	2
204	-20	4	5	2
223	-22	3	4	2
243	-24	3	4	1.5
263	-26	3	4	1.5
283	-28	3	4	1.5
303	-30	3	4	1.5
323	-32	3	4	1.5
343	-34	3	4	1.5

Micropac Industries cannot assume any responsibility for any circuits shown or represent that they are free from patent infringement.  
Micropac reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Mechanical Configuration



ELECTRICAL CONNECTIONS	
Case	$V_{IN}$
Pin 1	Ground
Pin 2	$V_{OUT}$

Figure 1, Power Derating





Figure 2, Typical Output Characteristics



Micropac Industries cannot assume any responsibility for any circuits shown or represent that they are free from patent infringement. Micropac reserves the right to make changes at any time in order to improve design and to supply the best product possible.