



Nut Torque:5 ~ 14Nm
 Operating Pressure:500gf ±200gf
 Operating Stroke:2.8mm±0.3
 Protection Grade:IP65
 Function:(ON)-OFF
 Contact:Silver Alloy
 Base:PBT
 Shell:SUS
 Button:SUS
 Terminal:Brass,silver Plating
 Lamp Type:LED
 Lamp Life:50000H
 Rating(Resistive load): 5A 250V AC
 Contact Resistance: 50mΩ MAX.
 Insulation Resistance: 100MΩ MIN.
 Dielectric Strength: 1500V AC 1 minute
 Electrical life: 50,000 cycles
 Mechanical life :200,000 cycles
 Operating Temperature: -20°C~80°C
 Relative Air Humidity:45%~85%
 Safety Approval:



D-SWITCH
 东莞市德松电子有限公司
 D-SWITCH ELECTRONICS CO.,LTD

公差 TOLERANCES .X± 0.5 .XX± 0.3 角度 ANGLE ±1° 单位 DIMENSION UNIT mm.

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECON NO.	版本 VERSION	核准 APPROVED BY	比例尺 SCALE	核对 CHECKED BY	日期 DATE	绘图 DRAWN BY	品名 TITLE	图号 DRAWING NO
				A0		1:1		2021.04.27	孙成	PBM-22M12-HT-U1-R5-S7S-D28-N33-A3	PBM-22M12-HT-U1-R5-S7S-D28-N33-A3_A0

版本 VER

变更说明 CHANGE DESCRIPTION

日期 DATE

ECON NO.

版本 VERSION

核准 APPROVED BY

比例尺 SCALE

核对 CHECKED BY

日期 DATE

绘图 DRAWN BY

品名 TITLE

图号 DRAWING NO