

## Han-Eco 10B Outd.-HSM2-f. DL-M32-cov.-gl



Image is for illustration purposes only. Please refer to product description.

Part number	19 43 310 0267
Specification	Han-Eco 10B Outd.-HSM2-f. DL-M32-cov.-gl
HARTING eCatalogue	<a href="https://b2b.harting.com/19433100267">https://b2b.harting.com/19433100267</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Eco® B
Type of hood/housing	Surface mounted housing
Description of hood/housing	With thermo-plastic cover With integrated cable gland

### Version

Locking type	Double locking lever (on the hood)
Size	10 B
Version	Side entry
Cable entry	2x M32

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP66
Clamping range	13 ... 21 mm

### Material properties

Material (hood/housing)	Polyamide (PA) Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	FPM
Colour (seal)	RAL 7001 (silver-grey)



Pushing Performance

## Material properties

Material flammability class acc. to UL 94	V-0
---	-----

## Specifications and approvals

Specifications	IEC 61984
	EN 45545-2 R22: HL1, HL2, HL3
	EN 45545-2 R23: HL1, HL2, HL3
	EN 45545-2 R24: HL1, HL2, HL3

CE	Yes
----	-----

## Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440202 Shell for industrial connectors