

Product data sheet

Characteristics

QO2401021

QO mini breaker, 40 A, 2 pole, 120/240 V, 10 kA, plug in, shunt trip

Product availability : Stock - Normally stocked in distribution facility



Price** : 256.00 USD



Main

| | |
|-----------------------|-------------------------------------|
| Product | Miniature circuit-breaker |
| Range | QO |
| Current Rating | 40 A |
| Voltage Rating | 120/240 V AC 120 V AC 48 V DC |
| Mounting Type | Plug-in |
| Number of Poles | 2P |
| Circuit Breaker Type | Standard |
| Ratings | HACR rated |
| Electrical Connection | Box lugs |
| Options | Shunt trip 120/208/240 V AC |

Complementary

| | |
|------------------------|--|
| Interrupt Rating | 10 kA 120/240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz 5 kA 48 V DC |
| Number of Panel Spaces | 3 |
| Wire Size | AWG 8...AWG 2 copper or aluminium |
| Tightening torque | 44.25 lbf.in (5 N.m) 0.02...0.04 in ² (10...25 mm ²) AWG 8...AWG 2) |
| Height | 79.25 mm (3.12 in) |
| Depth | 73.91 mm (2.91 in) |
| Width | 57.15 mm (2.25 in) |

Environment

| | |
|----------------|------------------|
| Certifications | UL listed CSA |
|----------------|------------------|

| | |
|----------------|----------------|
| Ambient Rating | 104 °F (40 °C) |
|----------------|----------------|

Ordering and shipping details

| | |
|---------------------|------------------------------------|
| Category | 00004 - QO,QOT 10-30A 1P;10-60A 2P |
| Discount Schedule | DE2A |
| GTIN | 00785901493983 |
| Package weight(Lbs) | 0.42 kg (0.92 lb(US)) |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|-----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|